

actions

Table comments: Stores action information.

Column	Type	Null	Default	Comments
aid	varchar(255)	No	0	Primary Key: Unique actions ID.
type	varchar(32)	No		The object that that action acts on (node, user, comment, system or custom types.)
callback	varchar(255)	No		The callback function that executes when the action runs.
parameters	longblob	No		Parameters to be passed to the callback function.
label	varchar(255)	No	0	Label of the action.

advanced_help_index

Table comments: Stores search index correlations for advanced help topics.

Column	Type	Null	Default	Comments
sid	int(10)	No		The primary key to give to the search engine for this topic.
module	varchar(255)	No		The module that owns this topic.
topic	varchar(255)	No		The topic id.
language	varchar(12)	No		The language this search index relates to.

authmap

Table comments: Stores distributed authentication mapping.

Column	Type	Null	Default	Comments
aid	int(10)	No		Primary Key: Unique authmap ID.
uid	int(11)	No	0	User's users.uid.
authname	varchar(128)	No		Unique authentication name.
module	varchar(128)	No		Module which is controlling the authentication.

batch

Table comments: Stores details about batches (processes that run in...

Column	Type	Null	Default	Comments
bid	int(10)	No		Primary Key: Unique batch ID.
token	varchar(64)	No		A string token generated against the current user's session id and the batch id, used to ensure that only the user who submitted the batch can effectively access it.
timestamp	int(11)	No		A Unix timestamp indicating when this batch was submitted for processing. Stale batches are purged at cron time.
batch	longblob	Yes	NULL	A serialized array containing the processing data for the batch.

block

Table comments: Stores block settings, such as region and visibility...

Column	Type	Null	Default	Comments
bid	int(11)	No		Primary Key: Unique block ID.
module	varchar(64)	No		The module from which the block originates; for example, 'user' for the Who's Online block, and 'block' for any custom blocks.
delta	varchar(32)	No	0	Unique ID for block within a module.
theme	varchar(64)	No		The theme under which the block settings apply.
status	tinyint(4)	No	0	Block enabled status. (1 = enabled, 0 = disabled)
weight	int(11)	No	0	Block weight within region.
region	varchar(64)	No		Theme region within which the block is set.
custom	tinyint(4)	No	0	Flag to indicate how users may control visibility of the block. (0 = Users cannot control, 1 = On by default, but can be hidden, 2 = Hidden by default, but can be

				shown)
visibility	tinyint(4)	No	0	Flag to indicate how to show blocks on pages. (0 = Show on all pages except listed pages, 1 = Show only on listed pages, 2 = Use custom PHP code to determine visibility)
pages	text	No		Contents of the "Pages" block; contains either a list of paths on which to include/exclude the block or PHP code, depending on "visibility" setting.
title	varchar(64)	No		Custom title for the block. (Empty string will use block default title, <none> will remove the title, text will cause block to use specified title.)
cache	tinyint(4)	No	1	Binary flag to indicate block cache mode. (-2: Custom cache, -1: Do not cache, 1: Cache per role, 2: Cache per user, 4: Cache per page, 8: Block cache global) See DRUPAL_CACHE_* constants in ../includes/common.inc for more detailed information.

block_current_search

Table comments: Sets up display criteria for blocks based on searcher

Column	Type	Null	Default	Comments
delta	varchar(32)	No		The block's unique delta within module, from block.delta.
searcher	varchar(128)	No		The machine-readable name of the searcher.

block_custom

Table comments: Stores contents of custom-made blocks.

Column	Type	Null	Default	Comments
bid	int(10)	No		The block's block.bid.
body	longtext	Yes	NULL	Block contents.
info	varchar(128)	No		Block description.
format	varchar(255)	Yes	NULL	The filter_format.format of the block body.

block_node_type

Table comments: Sets up display criteria for blocks based on content types

Column	Type	Null	Default	Comments
module	varchar(64)	No		The block's origin module, from block.module.
delta	varchar(32)	No		The block's unique delta within module, from block.delta.
type	varchar(32)	No		The machine-readable name of this type from node_type.type.

block_role

Table comments: Sets up access permissions for blocks based on user roles

Column	Type	Null	Default	Comments
module	varchar(64)	No		The block's origin module, from block.module.
delta	varchar(32)	No		The block's unique delta within module, from block.delta.
rid	int(10)	No		The user's role ID from users_roles.rid.

blocked_ips

Table comments: Stores blocked IP addresses.

Column	Type	Null	Default	Comments
iid	int(10)	No		Primary Key: unique ID for IP addresses.
ip	varchar(40)	No		IP address

cache

Table comments: Generic cache table for caching things not separated out...

Column	Type	Null	Default	Comments
cid	varchar(255)	No		Primary Key: Unique cache ID.
data	longblob	Yes	NULL	A collection of data to cache.
expire	int(11)	No	0	A Unix timestamp indicating when the cache entry should expire, or 0 for never.

created	int(11)	No	0	A Unix timestamp indicating when the cache entry was created.
serialized	smallint(6)	No	0	A flag to indicate whether content is serialized (1) or not (0).

cache_block

Table comments: Cache table for the Block module to store already built...

Column	Type	Null	Default	Comments
cid	varchar(255)	No		Primary Key: Unique cache ID.
data	longblob	Yes	NULL	A collection of data to cache.
expire	int(11)	No	0	A Unix timestamp indicating when the cache entry should expire, or 0 for never.
created	int(11)	No	0	A Unix timestamp indicating when the cache entry was created.
serialized	smallint(6)	No	0	A flag to indicate whether content is serialized (1) or not (0).

cache_bootstrap

Table comments: Cache table for data required to bootstrap Drupal, may be...

Column	Type	Null	Default	Comments
cid	varchar(255)	No		Primary Key: Unique cache ID.
data	longblob	Yes	NULL	A collection of data to cache.
expire	int(11)	No	0	A Unix timestamp indicating when the cache entry should expire, or 0 for never.
created	int(11)	No	0	A Unix timestamp indicating when the cache entry was created.
serialized	smallint(6)	No	0	A flag to indicate whether content is serialized (1) or not (0).

cache_commerce_shipping_rates

Table comments: Cache table for the temporary storage of base calculated...

Column	Type	Null	Default	Comments
cid	varchar(255)	No		Primary Key: Order ID and shipping method the rates are for.
data	longblob	Yes	NULL	A collection of data to cache.
expire	int(11)	No	0	A Unix timestamp indicating when the cache entry should expire, or 0 for never.
created	int(11)	No	0	A Unix timestamp indicating when the cache entry was created.
serialized	smallint(6)	No	0	A flag to indicate whether content is serialized (1) or not (0).

cache_entity_message

Table comments: Cache table used to store message entity records.

Column	Type	Null	Default	Comments
cid	varchar(255)	No		Primary Key: Unique cache ID.
data	longblob	Yes	NULL	A collection of data to cache.
expire	int(11)	No	0	A Unix timestamp indicating when the cache entry should expire, or 0 for never.
created	int(11)	No	0	A Unix timestamp indicating when the cache entry was created.
serialized	smallint(6)	No	0	A flag to indicate whether content is serialized (1) or not (0).

cache_entity_message_type

Table comments: Cache table used to store message_type entity records.

Column	Type	Null	Default	Comments
cid	varchar(255)	No		Primary Key: Unique cache ID.
data	longblob	Yes	NULL	A collection of data to cache.
expire	int(11)	No	0	A Unix timestamp indicating when the cache entry should expire, or 0 for never.
created	int(11)	No	0	A Unix timestamp indicating when the cache entry was created.
serialized	smallint(6)	No	0	A flag to indicate whether content is serialized (1) or not (0).

cache_entity_message_type_category

Table comments: Cache table used to store message_type_category entity...

Column	Type	Null	Default	Comments

cid	varchar(255)	No		Primary Key: Unique cache ID.
data	longblob	Yes	NULL	A collection of data to cache.
expire	int(11)	No	0	A Unix timestamp indicating when the cache entry should expire, or 0 for never.
created	int(11)	No	0	A Unix timestamp indicating when the cache entry was created.
serialized	smallint(6)	No	0	A flag to indicate whether content is serialized (1) or not (0).

cache_field

Table comments: Generic cache table for caching things not separated out...

Column	Type	Null	Default	Comments
cid	varchar(255)	No		Primary Key: Unique cache ID.
data	longblob	Yes	NULL	A collection of data to cache.
expire	int(11)	No	0	A Unix timestamp indicating when the cache entry should expire, or 0 for never.
created	int(11)	No	0	A Unix timestamp indicating when the cache entry was created.
serialized	smallint(6)	No	0	A flag to indicate whether content is serialized (1) or not (0).

cache_filter

Table comments: Cache table for the Filter module to store already...

Column	Type	Null	Default	Comments
cid	varchar(255)	No		Primary Key: Unique cache ID.
data	longblob	Yes	NULL	A collection of data to cache.
expire	int(11)	No	0	A Unix timestamp indicating when the cache entry should expire, or 0 for never.
created	int(11)	No	0	A Unix timestamp indicating when the cache entry was created.
serialized	smallint(6)	No	0	A flag to indicate whether content is serialized (1) or not (0).

cache_form

Table comments: Cache table for the form system to store recently built...

Column	Type	Null	Default	Comments
cid	varchar(255)	No		Primary Key: Unique cache ID.
data	longblob	Yes	NULL	A collection of data to cache.
expire	int(11)	No	0	A Unix timestamp indicating when the cache entry should expire, or 0 for never.
created	int(11)	No	0	A Unix timestamp indicating when the cache entry was created.
serialized	smallint(6)	No	0	A flag to indicate whether content is serialized (1) or not (0).

cache_image

Table comments: Cache table used to store information about image...

Column	Type	Null	Default	Comments
cid	varchar(255)	No		Primary Key: Unique cache ID.
data	longblob	Yes	NULL	A collection of data to cache.
expire	int(11)	No	0	A Unix timestamp indicating when the cache entry should expire, or 0 for never.
created	int(11)	No	0	A Unix timestamp indicating when the cache entry was created.
serialized	smallint(6)	No	0	A flag to indicate whether content is serialized (1) or not (0).

cache_libraries

Table comments: Cache table to store library information.

Column	Type	Null	Default	Comments
cid	varchar(255)	No		Primary Key: Unique cache ID.
data	longblob	Yes	NULL	A collection of data to cache.
expire	int(11)	No	0	A Unix timestamp indicating when the cache entry should expire, or 0 for never.
created	int(11)	No	0	A Unix timestamp indicating when the cache entry was created.
serialized	smallint(6)	No	0	A flag to indicate whether content is serialized (1) or not (0).

cache_menu

Table comments: Cache table for the menu system to store router...

Column	Type	Null	Default	Comments
cid	varchar(255)	No		Primary Key: Unique cache ID.
data	longblob	Yes	NULL	A collection of data to cache.
expire	int(11)	No	0	A Unix timestamp indicating when the cache entry should expire, or 0 for never.
created	int(11)	No	0	A Unix timestamp indicating when the cache entry was created.
serialized	smallint(6)	No	0	A flag to indicate whether content is serialized (1) or not (0).

cache_page

Table comments: Cache table used to store compressed pages for anonymous...

Column	Type	Null	Default	Comments
cid	varchar(255)	No		Primary Key: Unique cache ID.
data	longblob	Yes	NULL	A collection of data to cache.
expire	int(11)	No	0	A Unix timestamp indicating when the cache entry should expire, or 0 for never.
created	int(11)	No	0	A Unix timestamp indicating when the cache entry was created.
serialized	smallint(6)	No	0	A flag to indicate whether content is serialized (1) or not (0).

cache_path

Table comments: Cache table for path alias lookup.

Column	Type	Null	Default	Comments
cid	varchar(255)	No		Primary Key: Unique cache ID.
data	longblob	Yes	NULL	A collection of data to cache.
expire	int(11)	No	0	A Unix timestamp indicating when the cache entry should expire, or 0 for never.
created	int(11)	No	0	A Unix timestamp indicating when the cache entry was created.
serialized	smallint(6)	No	0	A flag to indicate whether content is serialized (1) or not (0).

cache_rules

Table comments: Cache table for the rules engine to store configured items.

Column	Type	Null	Default	Comments
cid	varchar(255)	No		Primary Key: Unique cache ID.
data	longblob	Yes	NULL	A collection of data to cache.
expire	int(11)	No	0	A Unix timestamp indicating when the cache entry should expire, or 0 for never.
created	int(11)	No	0	A Unix timestamp indicating when the cache entry was created.
serialized	smallint(6)	No	0	A flag to indicate whether content is serialized (1) or not (0).

cache_token

Table comments: Cache table for token information.

Column	Type	Null	Default	Comments
cid	varchar(255)	No		Primary Key: Unique cache ID.
data	longblob	Yes	NULL	A collection of data to cache.
expire	int(11)	No	0	A Unix timestamp indicating when the cache entry should expire, or 0 for never.
created	int(11)	No	0	A Unix timestamp indicating when the cache entry was created.
serialized	smallint(6)	No	0	A flag to indicate whether content is serialized (1) or not (0).

cache_update

Table comments: Cache table for the Update module to store information...

Column	Type	Null	Default	Comments
cid	varchar(255)	No		Primary Key: Unique cache ID.
data	longblob	Yes	NULL	A collection of data to cache.
expire	int(11)	No	0	A Unix timestamp indicating when the cache entry should expire, or 0 for never.
created	int(11)	No	0	A Unix timestamp indicating when the cache entry was created.
serialized	smallint(6)	No	0	A flag to indicate whether content is serialized (1) or not (0).

cache_views

Table comments: Generic cache table for caching things not separated out...

Column	Type	Null	Default	Comments
cid	varchar(255)	No		Primary Key: Unique cache ID.
data	longblob	Yes	NULL	A collection of data to cache.
expire	int(11)	No	0	A Unix timestamp indicating when the cache entry should expire, or 0 for never.
created	int(11)	No	0	A Unix timestamp indicating when the cache entry was created.
serialized	smallint(6)	No	0	A flag to indicate whether content is serialized (1) or not (0).

cache_views_data

Table comments: Cache table for views to store pre-rendered queries,...

Column	Type	Null	Default	Comments
cid	varchar(255)	No		Primary Key: Unique cache ID.
data	longblob	Yes	NULL	A collection of data to cache.
expire	int(11)	No	0	A Unix timestamp indicating when the cache entry should expire, or 0 for never.
created	int(11)	No	0	A Unix timestamp indicating when the cache entry was created.
serialized	smallint(6)	No	1	A flag to indicate whether content is serialized (1) or not (0).

comment

Table comments: Stores comments and associated data.

Column	Type	Null	Default	Comments
cid	int(11)	No		Primary Key: Unique comment ID.
pid	int(11)	No	0	The comment.cid to which this comment is a reply. If set to 0, this comment is not a reply to an existing comment.
nid	int(11)	No	0	The node.nid to which this comment is a reply.
uid	int(11)	No	0	The users.uid who authored the comment. If set to 0, this comment was created by an anonymous user.
subject	varchar(64)	No		The comment title.
hostname	varchar(128)	No		The author's host name.
created	int(11)	No	0	The time that the comment was created, as a Unix timestamp.
changed	int(11)	No	0	The time that the comment was last edited, as a Unix timestamp.
status	tinyint(3)	No	1	The published status of a comment. (0 = Not Published, 1 = Published)
thread	varchar(255)	No		The vancode representation of the comment's place in a thread.
name	varchar(60)	Yes	NULL	The comment author's name. Uses users.name if the user is logged in, otherwise uses the value typed into the comment form.
mail	varchar(64)	Yes	NULL	The comment author's e-mail address from the comment form, if user is anonymous, and the 'Anonymous users may/must leave their contact information' setting is turned on.
homepage	varchar(255)	Yes	NULL	The comment author's home page address from the comment form, if user is anonymous, and the 'Anonymous users may/must leave their contact information' setting is turned on.
language	varchar(12)	No		The languages.language of this comment.

commerce_addressbook_defaults

Table comments: Stores addressbook defaults by customer profile type.

Column	Type	Null	Default	Comments
cad_id	int(10)	No		Serial numeric ID of the default customer profile of a specific type.
profile_id	int(10)	No		Serial numeric ID of the customer profile in the local database.
type	varchar(255)	No		The customer profile type.
uid	int(10)	No		Serial numeric ID of the customer profile in the local database.

commerce_autosku_patterns

Table comments: TODO: please describe this table!

--	--	--	--	--

Column	Type	Null	Default	Comments
product_type	varchar(32)	No		Product type identifier.
pattern	varchar(255)	No		Token replacement pattern.
advanced	longblob	Yes	NULL	Serialized array of additional settings.

commerce_calculated_price

Table comments: Stores pre-calculated dynamic prices.

Column	Type	Null	Default	Comments
module	varchar(255)	No		The name of the module performing the calculation.
module_key	mediumtext	No		A module specific key useful for indicating the context of a particular calculation, e.g. the IDs of Rules evaluated to produce the calculated price.
entity_type	varchar(255)	No		The type of entity this price belongs to.
entity_id	int(10)	No	0	The entity ID of the object this price belongs to.
field_name	varchar(32)	No		The name of the field the calculated price relates to.
language	varchar(32)	No		The languages.language of the entity.
delta	int(10)	No	0	The sequence number for this data item, used for multi-value fields
amount	int(11)	No	0	The price amount.
currency_code	varchar(32)	No		The currency code for the price.
data	longtext	Yes	NULL	A serialized array of additional price data.
created	int(11)	No	0	The Unix timestamp when the price was calculated.

commerce_checkout_pane

Table comments: Checkout pane configuration data.

Column	Type	Null	Default	Comments
pane_id	varchar(255)	No		The machine readable name of the order state.
page	varchar(255)	No	1	The ID of the checkout page on which this pane appears.
fieldset	tinyint(4)	No	1	Boolean value indicating whether or not the pane should appear in a fieldset.
collapsible	tinyint(4)	No	0	Boolean value indicating whether or not the pane should appear collapsed.
collapsed	tinyint(4)	No	0	Boolean value indicating whether or not the pane should appear collapsed.
weight	smallint(6)	No	0	The sorting weight of the status for lists of statuses.
enabled	tinyint(4)	No	1	Boolean value indicating whether or not the pane is enabled.
review	tinyint(4)	No	1	Boolean value indicating whether or not the pane should appear on the checkout review.

commerce_customer_profile

Table comments: The base table for customer profiles.

Column	Type	Null	Default	Comments
profile_id	int(10)	No		The primary identifier for a customer profile.
revision_id	int(10)	Yes	NULL	The current commerce_customer_profile_revision.revision_id version identifier.
type	varchar(255)	No		The commerce_customer_profile_type.type of this profile.
uid	int(11)	No	0	The users.uid that this profile belongs to.
status	int(11)	No	0	Boolean indicating whether the profile is active or not.
created	int(11)	No	0	The Unix timestamp when the profile was created.
changed	int(11)	No	0	The Unix timestamp when the profile was most recently saved.
data	longblob	Yes	NULL	A serialized array of additional data.

commerce_customer_profile_revision

Table comments: Saves information about each saved revision of a commerce...

Column	Type	Null	Default	Comments
profile_id	int(10)	No	0	The commerce_customer_profile.customer_id of the profile this revision belongs to.
revision_id	int(10)	No		The primary identifier for this revision.
revision_uid	int(11)	No	0	The users.uid that created this profile at this revision.
status	int(11)	No	0	Boolean indicating whether the profile is active or not.

log	longtext	No		The log entry explaining the changes in this version.
revision_timestamp	int(11)	No	0	The Unix timestamp when this revision was created.
data	longblob	Yes	NULL	A serialized array of additional data.

commerce_discount

Table comments: The base table for discounts.

Column	Type	Null	Default	Comments
discount_id	int(11)	No		The internal identifier for any discount.
name	varchar(64)	No		The machine name of the discount.
label	varchar(255)	No		The label of the discount.
type	varchar(255)	No		The discount type (bundle).
enabled	tinyint(4)	No	1	Whether the discount is enabled.
status	tinyint(4)	No	1	The exportable status of the entity.
module	varchar(255)	Yes	NULL	The name of the providing module if the entity has been defined in code.

commerce_discount_offer

Table comments: The base table for discount offers.

Column	Type	Null	Default	Comments
discount_offer_id	int(11)	No		The internal identifier for any discount offer.
type	varchar(255)	No		The discount offer type (bundle).

commerce_flat_rate_service

Table comments: Stores information about shipping services created...

Column	Type	Null	Default	Comments
name	varchar(32)	No		The machine-name of the flat rate service.
title	varchar(255)	No		The human-readable title of the flat rate service.
display_title	varchar(255)	No		The title of the flat rate service displayed to customers.
description	mediumtext	No		A brief description of the flat rate service.
rules_component	tinyint(4)	No	0	Boolean indicating whether or not this service should have a default Rules component for enabling it for orders.
amount	int(11)	No	0	The amount of the base rate of the service.
currency_code	varchar(32)	No		The currency code of the base rate of the service.
data	longtext	Yes	NULL	A serialized array of additional data.

commerce_line_item

Table comments: The base table for line items.

Column	Type	Null	Default	Comments
line_item_id	int(10)	No		The primary identifier for a line item.
order_id	int(11)	No	0	The unique ID of the order the line item belongs to.
type	varchar(255)	No		The module defined type of this line item.
line_item_label	varchar(255)	No		The merchant defined label for a line item.
quantity	decimal(10,2)	No	0.00	
created	int(11)	No	0	The Unix timestamp when the line item was created.
changed	int(11)	No	0	The Unix timestamp when the line item was most recently saved.
data	longblob	Yes	NULL	A serialized array of additional data.

commerce_order

Table comments: The base table for orders.

Column	Type	Null	Default	Comments
order_id	int(10)	No		The primary identifier for an order.
order_number	varchar(255)	Yes	NULL	The order number displayed to the customer.
revision_id	int(10)	Yes	NULL	The current commerce_order_revision.revision_id version identifier.
type	varchar(255)	No		The type of this order.

uid	int(11)	No	0	The users.uid that owns this order.
mail	varchar(255)	No		The e-mail address associated with the order.
status	varchar(255)	No		The status name of this order.
created	int(11)	No	0	The Unix timestamp when the order was created.
changed	int(11)	No	0	The Unix timestamp when the order was most recently saved.
hostname	varchar(128)	No		The IP address that created this order.
data	longblob	Yes	NULL	A serialized array of additional data.

commerce_order_revision

Table comments: Saves information about each saved revision of a commerce...

Column	Type	Null	Default	Comments
order_id	int(10)	No	0	The commerce_order.order_id of the order this revision belongs to.
order_number	varchar(255)	Yes	NULL	The order number displayed to the customer for this revision.
revision_id	int(10)	No		The primary identifier for this revision.
revision_uid	int(11)	No	0	The users.uid that owns the order at this revision.
mail	varchar(255)	No		The e-mail address associated with the order at this revision.
status	varchar(255)	No		The status name of this revision.
log	longtext	No		The log entry explaining the changes in this version.
revision_timestamp	int(11)	No	0	The Unix timestamp when this revision was created.
revision_hostname	varchar(128)	No		The IP address that created this order.
data	longblob	Yes	NULL	A serialized array of additional data.

commerce_payment_transaction

Table comments: Transaction information for every attempted payment.

Column	Type	Null	Default	Comments
transaction_id	int(10)	No		The primary identifier for a transaction.
revision_id	int(10)	Yes	NULL	The current commerce_payment_transaction_revision.revision_id version identifier.
uid	int(11)	No	0	The users.uid that created this transaction.
order_id	int(10)	No	0	The commerce_order.order_id of the order this payment is for.
payment_method	varchar(128)	No		The payment method method_id for this transaction.
instance_id	varchar(255)	No		The payment method instance ID for this transaction.
remote_id	varchar(255)	No		The remote identifier for this transaction.
message	longtext	No		The human-readable message associated to this transaction.
message_variables	longblob	No		The variables associated with the human-readable message.
amount	int(11)	No	0	The amount of this transaction.
currency_code	varchar(32)	No		The currency code for the price.
status	varchar(128)	No		The status of this transaction (pending, success, or failure).
remote_status	varchar(128)	No		The status of the transaction at the payment provider.
payload	longblob	No		The payment-gateway specific payload associated with this transaction.
created	int(11)	No	0	The Unix timestamp when this transaction was created.
changed	int(11)	No	0	The Unix timestamp when this transaction was last changed.
data	longblob	Yes	NULL	A serialized array of additional data.

commerce_payment_transaction_revision

Table comments: Saves information about each saved revision of a commerce...

Column	Type	Null	Default	Comments
transaction_id	int(10)	No	0	The primary identifier for a transaction.
revision_id	int(10)	No		The current commerce_payment_transaction_revision.revision_id version identifier.
revision_uid	int(11)	No	0	The users.uid that created this revision.
remote_id	varchar(255)	No		The remote identifier for this transaction.
message	longtext	No		The human-readable message associated to this transaction.
message_variables	longblob	No		The variables associated with the human-readable message.

amount	int(11)	No	0	The amount of this transaction.
currency_code	varchar(32)	No		The currency code for the price.
status	varchar(128)	No		The status of this transaction (pending, success, or failure).
remote_status	varchar(128)	No		The status of the transaction at the payment provider.
log	longtext	No		The log entry explaining the changes in this version.
revision_timestamp	int(11)	No	0	The Unix timestamp when this revision was created.
data	longblob	Yes	NULL	A serialized array of additional data.

commerce_product

Table comments: The base table for products.

Column	Type	Null	Default	Comments
product_id	int(10)	No		The primary identifier for a product, used internally only.
revision_id	int(10)	Yes	NULL	The current commerce_product_revision.revision_id version identifier.
sku	varchar(255)	No		The unique, human-readable identifier for a product.
title	varchar(255)	No		The title of this product, always treated as non-markup plain text.
type	varchar(255)	No		The commerce_product_type.type of this product.
language	varchar(32)	No		The languages.language of this product.
uid	int(11)	No	0	The users.uid that created this product.
status	tinyint(4)	No	1	Boolean indicating whether or not the product appears in lists and may be added to orders.
created	int(11)	No	0	The Unix timestamp when the product was created.
changed	int(11)	No	0	The Unix timestamp when the product was most recently saved.
data	longblob	Yes	NULL	A serialized array of additional data.

commerce_product_revision

Table comments: Saves information about each saved revision of a commerce...

Column	Type	Null	Default	Comments
product_id	int(10)	No	0	The commerce_product.product_id of the product this revision belongs to.
revision_id	int(10)	No		The primary identifier for this revision.
sku	varchar(255)	No		The unique, human-readable identifier of a product for this revision.
title	varchar(255)	No		The title of this product for this revision
revision_uid	int(11)	No	0	The users.uid that owns the product at this revision.
status	tinyint(4)	No	1	The status of this revision.
log	longtext	No		The log entry explaining the changes in this version.
revision_timestamp	int(11)	No	0	The Unix timestamp when this revision was created.
data	longblob	Yes	NULL	A serialized array of additional data for this revision.

commerce_product_type

Table comments: Stores information about commerce_product types created...

Column	Type	Null	Default	Comments
type	varchar(32)	No		The machine-readable name of this type.
name	varchar(255)	No		The human-readable name of this type.
description	mediumtext	No		A brief description of this type.
help	mediumtext	No		Help information shown to the user when creating a commerce_product of this type.
revision	tinyint(4)	No	1	Determine whether to create a new revision when a product of this type is updated.

commerce_tax_rate

Table comments: Stores information about tax rates created via Tax UI.

Column	Type	Null	Default	Comments
name	varchar(64)	No		The machine-name of this rate.
title	varchar(255)	No		The administrative title of this rate.

display_title	varchar(255)	No		The front end display title of this rate.
description	mediumtext	No		A brief description of this rate.
rate	varchar(64)	No	0	The percentage used to calculate this tax expressed as a decimal.
type	varchar(64)	No		The machine-name of the rate's commerce_tax_type.
default_rules_component	tinyint(4)	No	0	Boolean indicating whether or not this rate should have a default Rules component for applying it to products.
module	varchar(255)	No		The name of the module that defines this tax type.

commerce_tax_type

Table comments: Stores information about tax types created via Tax UI.

Column	Type	Null	Default	Comments
name	varchar(64)	No		The machine-name of this type.
title	varchar(255)	No		The administrative title of this type.
display_title	varchar(255)	No		The front end display title of this type.
description	mediumtext	No		A brief description of this type.
display_inclusive	tinyint(4)	No	0	Boolean indicating whether or not taxes of this type display inclusively in product prices.
round_mode	tinyint(4)	No	0	Integer indicating what type of rounding (if any) should be done for taxes of this type.
module	varchar(255)	No		The name of the module that defines this tax type.

connector_info

Table comments: connector_info

Column	Type	Null	Default	Comments
uid	int(10)	No	0	The id of the user
type	varchar(80)	No		The type of property - eg. 'real name'
value	varchar(80)	Yes		The value of the property
max_life	int(10)	Yes	0	The Unix timestamp when info latest needs to be refreshed
failure_level	tinyint(3)	Yes	0	The level of failure

connector_user

Table comments: connector_user

Column	Type	Null	Default	Comments
uid	int(10)	No	0	The id of the user
primary_connection	varchar(128)	No		The primary connection for the user

ctools_css_cache

Table comments: A special cache used to store CSS that must be non-volatile.

Column	Type	Null	Default	Comments
cid	varchar(128)	No		The CSS ID this cache object belongs to.
filename	varchar(255)	Yes	NULL	The filename this CSS is stored in.
css	longtext	Yes	NULL	CSS being stored.
filter	tinyint(4)	Yes	NULL	Whether or not this CSS needs to be filtered.

ctools_object_cache

Table comments: A special cache used to store objects that are being...

Column	Type	Null	Default	Comments
sid	varchar(64)	No		The session ID this cache object belongs to.
name	varchar(128)	No		The name of the object this cache is attached to.
obj	varchar(32)	No		The type of the object this cache is attached to; this essentially represents the owner so that several sub-systems can use this cache.
updated	int(10)	No	0	The time this cache was created or updated.

data	longtext	Yes	NULL	Serialized data being stored.
------	----------	-----	------	-------------------------------

current_search

Table comments: Current search block configurations.

Column	Type	Null	Default	Comments
name	varchar(255)	No		The machine readable name of the configuration.
label	varchar(255)	No		The human readable name of the configuration.
settings	text	Yes	NULL	Serialized storage of general settings.

date_format_locale

Table comments: Stores configured date formats for each locale.

Column	Type	Null	Default	Comments
format	varchar(100)	No		The date format string.
type	varchar(64)	No		The date format type, e.g. medium.
language	varchar(12)	No		A languages.language for this format to be used with.

date_format_type

Table comments: Stores configured date format types.

Column	Type	Null	Default	Comments
type	varchar(64)	No		The date format type, e.g. medium.
title	varchar(255)	No		The human readable name of the format type.
locked	tinyint(4)	No	0	Whether or not this is a system provided format.

date_formats

Table comments: Stores configured date formats.

Column	Type	Null	Default	Comments
dfid	int(10)	No		The date format identifier.
format	varchar(100)	No		The date format string.
type	varchar(64)	No		The date format type, e.g. medium.
locked	tinyint(4)	No	0	Whether or not this format can be modified.

facetapi

Table comments: Facet configurations.

Column	Type	Null	Default	Comments
name	varchar(255)	No		The machine readable name of the configuration.
searcher	varchar(64)	No		The machine readable name of the searcher.
realm	varchar(64)	No		The machine readable name of the realm.
facet	varchar(255)	No		The machine readable name of the facet.
enabled	tinyint(4)	No	0	Whether the facet is enabled.
settings	blob	Yes	NULL	Serialized storage of general settings.

field_config

Table comments: field_config

Column	Type	Null	Default	Comments
id	int(11)	No		The primary identifier for a field
field_name	varchar(32)	No		The name of this field. Non-deleted field names are unique, but multiple deleted fields can have the same name.
type	varchar(128)	No		The type of this field.
module	varchar(128)	No		The module that implements the field type.
active	tinyint(4)	No	0	Boolean indicating whether the module that implements the field type is enabled.
storage_type	varchar(128)	No		The storage backend for the field.

storage_module	varchar(128)	No		The module that implements the storage backend.
storage_active	tinyint(4)	No	0	Boolean indicating whether the module that implements the storage backend is enabled.
locked	tinyint(4)	No	0	@TODO
data	longblob	No		Serialized data containing the field properties that do not warrant a dedicated column.
cardinality	tinyint(4)	No	0	
translatable	tinyint(4)	No	0	
deleted	tinyint(4)	No	0	

field_config_instance

Table comments: field_config_instance

Column	Type	Null	Default	Comments
id	int(11)	No		The primary identifier for a field instance
field_id	int(11)	No		The identifier of the field attached by this instance
field_name	varchar(32)	No		
entity_type	varchar(32)	No		
bundle	varchar(128)	No		
data	longblob	No		
deleted	tinyint(4)	No	0	

field_data_body

Table comments: Data storage for field 19 (body)

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	Yes	NULL	The entity revision id this data is attached to, or NULL if the entity type is not versioned
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields
body_value	longtext	Yes	NULL	
body_format	varchar(255)	Yes	NULL	

field_data_comment_body

Table comments: Data storage for field 20 (comment_body)

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	Yes	NULL	The entity revision id this data is attached to, or NULL if the entity type is not versioned
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields
comment_body_value	longtext	Yes	NULL	
comment_body_format	varchar(255)	Yes	NULL	

field_data_commerce_customer_address

Table comments: Data storage for field 1 (commerce_customer_address)

Column	Type	Null	Default	Comments

entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	Yes	NULL	The entity revision id this data is attached to, or NULL if the entity type is not versioned
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields
commerce_customer_address_country	varchar(2)	Yes		Two letter ISO country code of this address.
commerce_customer_address_administrative_area	varchar(255)	Yes		The administrative area of this address. (i.e. State/Province)
commerce_customer_address_sub_administrative_area	varchar(255)	Yes		The sub administrative area of this address.
commerce_customer_address_locality	varchar(255)	Yes		The locality of this address. (i.e. City)
commerce_customer_address_dependent_locality	varchar(255)	Yes		The dependent locality of this address.
commerce_customer_address_postal_code	varchar(255)	Yes		The postal code of this address.
commerce_customer_address_thoroughfare	varchar(255)	Yes		The thoroughfare of this address. (i.e. Street address)
commerce_customer_address_premise	varchar(255)	Yes		The premise of this address. (i.e. Apartment / Suite number)
commerce_customer_address_sub_premise	varchar(255)	Yes		The sub_premise of this address.
commerce_customer_address_organisation_name	varchar(255)	Yes		Contents of a primary OrganisationName element in the xNL XML.
commerce_customer_address_name_line	varchar(255)	Yes		Contents of a primary NameLine element in the xNL XML.
commerce_customer_address_first_name	varchar(255)	Yes		Contents of the FirstName element of a primary PersonName element in the xNL XML.
commerce_customer_address_last_name	varchar(255)	Yes		Contents of the LastName element of a primary PersonName element in the xNL XML.
commerce_customer_address_data	longtext	Yes	NULL	Additional data for this address.

field_data_commerce_customer_billing

Table comments: Data storage for field 4 (commerce_customer_billing)

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	Yes	NULL	The entity revision id this data is attached to, or NULL if the entity type is not versioned
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields
commerce_customer_billing_profile_id	int(10)	Yes	NULL	

field_data_commerce_customer_shipping

Table comments: Data storage for field 16 (commerce_customer_shipping)

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	Yes	NULL	The entity revision id this data is attached to, or NULL if the entity type is not versioned
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields
commerce_customer_shipping_profile_id	int(10)	Yes	NULL	

field_data_commerce_discount_date

Table comments: Data storage for field 14 (commerce_discount_date)

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	Yes	NULL	The entity revision id this data is attached to, or NULL if the entity type is not versioned
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields
commerce_discount_date_value	int(11)	Yes	NULL	
commerce_discount_date_value2	int(11)	Yes	NULL	

field_data_commerce_discount_offer

Table comments: Data storage for field 10 (commerce_discount_offer)

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	Yes	NULL	The entity revision id this data is attached to, or NULL if the entity type is not versioned
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields
commerce_discount_offer_target_id	int(10)	No		The id of the target entity.

field_data_commerce_discounts

Table comments: Data storage for field 13 (commerce_discounts)

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted

entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	Yes	NULL	The entity revision id this data is attached to, or NULL if the entity type is not versioned
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields
commerce_discounts_target_id	int(10)	No		The id of the target entity.

field_data_commerce_display_path

Table comments: Data storage for field 8 (commerce_display_path)

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	Yes	NULL	The entity revision id this data is attached to, or NULL if the entity type is not versioned
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields
commerce_display_path_value	varchar(255)	Yes	NULL	
commerce_display_path_format	varchar(255)	Yes	NULL	

field_data_commerce_fixed_amount

Table comments: Data storage for field 11 (commerce_fixed_amount)

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	Yes	NULL	The entity revision id this data is attached to, or NULL if the entity type is not versioned
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields
commerce_fixed_amount_amount	int(11)	No	0	The price amount.
commerce_fixed_amount_currency_code	varchar(32)	No		The currency code for the price.
commerce_fixed_amount_data	longtext	Yes	NULL	A serialized array of additional price data.

field_data_commerce_line_items

Table comments: Data storage for field 2 (commerce_line_items)

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	Yes	NULL	The entity revision id this data is attached to, or NULL if the entity type is not versioned
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-

				value fields
commerce_line_items_line_item_id	int(10)	Yes	NULL	

field_data_commerce_order_total

Table comments: Data storage for field 3 (commerce_order_total)

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	Yes	NULL	The entity revision id this data is attached to, or NULL if the entity type is not versioned
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields
commerce_order_total_amount	int(11)	No	0	The price amount.
commerce_order_total_currency_code	varchar(32)	No		The currency code for the price.
commerce_order_total_data	longtext	Yes	NULL	A serialized array of additional price data.

field_data_commerce_percentage

Table comments: Data storage for field 12 (commerce_percentage)

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	Yes	NULL	The entity revision id this data is attached to, or NULL if the entity type is not versioned
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields
commerce_percentage_value	decimal(10,2)	Yes	NULL	

field_data_commerce_price

Table comments: Data storage for field 9 (commerce_price)

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	Yes	NULL	The entity revision id this data is attached to, or NULL if the entity type is not versioned
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields
commerce_price_amount	int(11)	No	0	The price amount.
commerce_price_currency_code	varchar(32)	No		The currency code for the price.
commerce_price_data	longtext	Yes	NULL	A serialized array of additional price data.

field_data_commerce_product

Table comments: Data storage for field 7 (commerce_product)

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	Yes	NULL	The entity revision id this data is attached to, or NULL if the entity type is not versioned
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields
commerce_product_product_id	int(10)	Yes	NULL	

field_data_commerce_shipping_service

Table comments: Data storage for field 15 (commerce_shipping_service)

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	Yes	NULL	The entity revision id this data is attached to, or NULL if the entity type is not versioned
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields
commerce_shipping_service_value	varchar(255)	Yes	NULL	

field_data_commerce_total

Table comments: Data storage for field 6 (commerce_total)

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	Yes	NULL	The entity revision id this data is attached to, or NULL if the entity type is not versioned
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields
commerce_total_amount	int(11)	No	0	The price amount.
commerce_total_currency_code	varchar(32)	No		The currency code for the price.
commerce_total_data	longtext	Yes	NULL	A serialized array of additional price data.

field_data_commerce_unit_price

Table comments: Data storage for field 5 (commerce_unit_price)

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted

entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	Yes	NULL	The entity revision id this data is attached to, or NULL if the entity type is not versioned
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields
commerce_unit_price_amount	int(11)	No	0	The price amount.
commerce_unit_price_currency_code	varchar(32)	No		The currency code for the price.
commerce_unit_price_data	longtext	Yes	NULL	A serialized array of additional price data.

field_data_field_bag_size

Table comments: Data storage for field 31 (field_bag_size)

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	Yes	NULL	The entity revision id this data is attached to, or NULL if the entity type is not versioned
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields
field_bag_size_tid	int(10)	Yes	NULL	

field_data_field_blog_category

Table comments: Data storage for field 25 (field_blog_category)

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	Yes	NULL	The entity revision id this data is attached to, or NULL if the entity type is not versioned
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields
field_blog_category_tid	int(10)	Yes	NULL	

field_data_field_brand

Table comments: Data storage for field 38 (field_brand)

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	Yes	NULL	The entity revision id this data is attached to, or NULL if the entity type is not versioned
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields
field_brand_tid	int(10)	Yes	NULL	

field_data_field_category

Table comments: Data storage for field 39 (field_category)

Column	Type	Null	Default	Comments
--------	------	------	---------	----------

entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	Yes	NULL	The entity revision id this data is attached to, or NULL if the entity type is not versioned
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields
field_category_tid	int(10)	Yes	NULL	

field_data_field_category_color

Table comments: Data storage for field 43 (field_category_color)

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	Yes	NULL	The entity revision id this data is attached to, or NULL if the entity type is not versioned
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields
field_category_color_value	varchar(7)	Yes	NULL	
field_category_color_format	varchar(255)	Yes	NULL	

field_data_field_collection

Table comments: Data storage for field 40 (field_collection)

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	Yes	NULL	The entity revision id this data is attached to, or NULL if the entity type is not versioned
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields
field_collection_tid	int(10)	Yes	NULL	

field_data_field_color

Table comments: Data storage for field 32 (field_color)

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	Yes	NULL	The entity revision id this data is attached to, or NULL if the entity type is not versioned
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields
field_color_tid	int(10)	Yes	NULL	

field_data_field_gender

Table comments: Data storage for field 41 (field_gender)

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	Yes	NULL	The entity revision id this data is attached to, or NULL if the entity type is not versioned
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields
field_gender_tid	int(10)	Yes	NULL	

field_data_field_hat_size

Table comments: Data storage for field 34 (field_hat_size)

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	Yes	NULL	The entity revision id this data is attached to, or NULL if the entity type is not versioned
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields
field_hat_size_tid	int(10)	Yes	NULL	

field_data_field_headline

Table comments: Data storage for field 44 (field_headline)

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	Yes	NULL	The entity revision id this data is attached to, or NULL if the entity type is not versioned
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields
field_headline_value	varchar(20)	Yes	NULL	
field_headline_format	varchar(255)	Yes	NULL	

field_data_field_image

Table comments: Data storage for field 26 (field_image)

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	Yes	NULL	The entity revision id this data is attached to, or NULL if the entity type is not versioned
language	varchar(32)	No		The language for this data item.

delta	int(10)	No		The sequence number for this data item, used for multi-value fields
field_image_fid	int(10)	Yes	NULL	The file_managed.fid being referenced in this field.
field_image_alt	varchar(512)	Yes	NULL	Alternative image text, for the image's 'alt' attribute.
field_image_title	varchar(1024)	Yes	NULL	Image title text, for the image's 'title' attribute.
field_image_width	int(10)	Yes	NULL	The width of the image in pixels.
field_image_height	int(10)	Yes	NULL	The height of the image in pixels.

field_data_field_images

Table comments: Data storage for field 33 (field_images)

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	Yes	NULL	The entity revision id this data is attached to, or NULL if the entity type is not versioned
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields
field_images_fid	int(10)	Yes	NULL	The file_managed.fid being referenced in this field.
field_images_alt	varchar(512)	Yes	NULL	Alternative image text, for the image's 'alt' attribute.
field_images_title	varchar(1024)	Yes	NULL	Image title text, for the image's 'title' attribute.
field_images_width	int(10)	Yes	NULL	The width of the image in pixels.
field_images_height	int(10)	Yes	NULL	The height of the image in pixels.

field_data_field_link

Table comments: Data storage for field 29 (field_link)

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	Yes	NULL	The entity revision id this data is attached to, or NULL if the entity type is not versioned
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields
field_link_url	varchar(2048)	Yes	NULL	
field_link_title	varchar(255)	Yes	NULL	
field_link_attributes	mediumtext	Yes	NULL	

field_data_field_product

Table comments: Data storage for field 42 (field_product)

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	Yes	NULL	The entity revision id this data is attached to, or NULL if the entity type is not versioned
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields
field_product_product_id	int(10)	Yes	NULL	

field_data_field_shoe_size

Table comments: Data storage for field 35 (field_shoe_size)

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	Yes	NULL	The entity revision id this data is attached to, or NULL if the entity type is not versioned
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields
field_shoe_size_tid	int(10)	Yes	NULL	

field_data_field_storage_capacity

Table comments: Data storage for field 36 (field_storage_capacity)

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	Yes	NULL	The entity revision id this data is attached to, or NULL if the entity type is not versioned
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields
field_storage_capacity_tid	int(10)	Yes	NULL	

field_data_field_tagline

Table comments: Data storage for field 30 (field_tagline)

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	Yes	NULL	The entity revision id this data is attached to, or NULL if the entity type is not versioned
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields
field_tagline_value	varchar(80)	Yes	NULL	
field_tagline_format	varchar(255)	Yes	NULL	

field_data_field_tags

Table comments: Data storage for field 27 (field_tags)

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	Yes	NULL	The entity revision id this data is attached to, or NULL if the entity type is not versioned
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields

field_tags_tid	int(10)	Yes	NULL	
----------------	---------	-----	------	--

field_data_field_top_size

Table comments: Data storage for field 37 (field_top_size)

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	Yes	NULL	The entity revision id this data is attached to, or NULL if the entity type is not versioned
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields
field_top_size_tid	int(10)	Yes	NULL	

field_data_message_commerce_body

Table comments: Data storage for field 24 (message_commerce_body)

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	Yes	NULL	The entity revision id this data is attached to, or NULL if the entity type is not versioned
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields
message_commerce_body_value	longtext	Yes	NULL	
message_commerce_body_format	varchar(255)	Yes	NULL	

field_data_message_commerce_line_item

Table comments: Data storage for field 22 (message_commerce_line_item)

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	Yes	NULL	The entity revision id this data is attached to, or NULL if the entity type is not versioned
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields
message_commerce_line_item_target_id	int(10)	No		The id of the target entity.

field_data_message_commerce_order

Table comments: Data storage for field 21 (message_commerce_order)

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance

deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	Yes	NULL	The entity revision id this data is attached to, or NULL if the entity type is not versioned
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields
message_commerce_order_target_id	int(10)	No		The id of the target entity.

field_data_message_commerce_payment

Table comments: Data storage for field 23 (message_commerce_payment)

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	Yes	NULL	The entity revision id this data is attached to, or NULL if the entity type is not versioned
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields
message_commerce_payment_target_id	int(10)	No		The id of the target entity.

field_data_message_order_display_name

Table comments: Data storage for field 18 (message_order_display_name)

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	Yes	NULL	The entity revision id this data is attached to, or NULL if the entity type is not versioned
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields
message_order_display_name_value	varchar(255)	Yes	NULL	
message_order_display_name_format	varchar(255)	Yes	NULL	

field_data_message_text

Table comments: Data storage for field 17 (message_text)

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	Yes	NULL	The entity revision id this data is attached to, or NULL if the entity type is not versioned
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields
message_text_value	longtext	Yes	NULL	
message_text_format	varchar(255)	Yes	NULL	

field_data_title_field

Table comments: Data storage for field 28 (title_field)

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	Yes	NULL	The entity revision id this data is attached to, or NULL if the entity type is not versioned
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields
title_field_value	varchar(255)	Yes	NULL	
title_field_format	varchar(255)	Yes	NULL	

field_revision_body

Table comments: Revision archive storage for field 19 (body)

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	No		The entity revision id this data is attached to
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields
body_value	longtext	Yes	NULL	
body_format	varchar(255)	Yes	NULL	

field_revision_comment_body

Table comments: Revision archive storage for field 20 (comment_body)

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	No		The entity revision id this data is attached to
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields
comment_body_value	longtext	Yes	NULL	
comment_body_format	varchar(255)	Yes	NULL	

field_revision_commerce_customer_address

Table comments: Revision archive storage for field 1 (commerce_customer...

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached

				to
revision_id	int(10)	No		The entity revision id this data is attached to
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields
commerce_customer_address_country	varchar(2)	Yes		Two letter ISO country code of this address.
commerce_customer_address_administrative_area	varchar(255)	Yes		The administrative area of this address. (i.e. State/Province)
commerce_customer_address_sub_administrative_area	varchar(255)	Yes		The sub administrative area of this address.
commerce_customer_address_locality	varchar(255)	Yes		The locality of this address. (i.e. City)
commerce_customer_address_dependent_locality	varchar(255)	Yes		The dependent locality of this address.
commerce_customer_address_postal_code	varchar(255)	Yes		The postal code of this address.
commerce_customer_address_thoroughfare	varchar(255)	Yes		The thoroughfare of this address. (i.e. Street address)
commerce_customer_address_premise	varchar(255)	Yes		The premise of this address. (i.e. Apartment / Suite number)
commerce_customer_address_sub_premise	varchar(255)	Yes		The sub_premise of this address.
commerce_customer_address_organisation_name	varchar(255)	Yes		Contents of a primary OrganisationName element in the xNL XML.
commerce_customer_address_name_line	varchar(255)	Yes		Contents of a primary NameLine element in the xNL XML.
commerce_customer_address_first_name	varchar(255)	Yes		Contents of the FirstName element of a primary PersonName element in the xNL XML.
commerce_customer_address_last_name	varchar(255)	Yes		Contents of the LastName element of a primary PersonName element in the xNL XML.
commerce_customer_address_data	longtext	Yes	NULL	Additional data for this address.

field_revision_commerce_customer_billing

Table comments: Revision archive storage for field 4 (commerce_customer...

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	No		The entity revision id this data is attached to
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields
commerce_customer_billing_profile_id	int(10)	Yes	NULL	

field_revision_commerce_customer_shipping

Table comments: Revision archive storage for field 16 (commerce_customer...

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted

entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	No		The entity revision id this data is attached to
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields
commerce_customer_shipping_profile_id	int(10)	Yes	NULL	

field_revision_commerce_discount_date

Table comments: Revision archive storage for field 14 (commerce_discount...

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	No		The entity revision id this data is attached to
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields
commerce_discount_date_value	int(11)	Yes	NULL	
commerce_discount_date_value2	int(11)	Yes	NULL	

field_revision_commerce_discount_offer

Table comments: Revision archive storage for field 10 (commerce_discount...

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	No		The entity revision id this data is attached to
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields
commerce_discount_offer_target_id	int(10)	No		The id of the target entity.

field_revision_commerce_discounts

Table comments: Revision archive storage for field 13 (commerce_discounts)

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	No		The entity revision id this data is attached to
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields
commerce_discounts_target_id	int(10)	No		The id of the target entity.

field_revision_commerce_display_path

Table comments: Revision archive storage for field 8 (commerce_display_path)

--	--	--	--	--

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	No		The entity revision id this data is attached to
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields
commerce_display_path_value	varchar(255)	Yes	NULL	
commerce_display_path_format	varchar(255)	Yes	NULL	

field_revision_commerce_fixed_amount

Table comments: Revision archive storage for field 11 (commerce_fixed...

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	No		The entity revision id this data is attached to
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields
commerce_fixed_amount_amount	int(11)	No	0	The price amount.
commerce_fixed_amount_currency_code	varchar(32)	No		The currency code for the price.
commerce_fixed_amount_data	longtext	Yes	NULL	A serialized array of additional price data.

field_revision_commerce_line_items

Table comments: Revision archive storage for field 2 (commerce_line_items)

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	No		The entity revision id this data is attached to
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields
commerce_line_items_line_item_id	int(10)	Yes	NULL	

field_revision_commerce_order_total

Table comments: Revision archive storage for field 3 (commerce_order_total)

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	No		The entity revision id this data is attached to

language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields
commerce_order_total_amount	int(11)	No	0	The price amount.
commerce_order_total_currency_code	varchar(32)	No		The currency code for the price.
commerce_order_total_data	longtext	Yes	NULL	A serialized array of additional price data.

field_revision_commerce_percentage

Table comments: Revision archive storage for field 12 (commerce_percentage)

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	No		The entity revision id this data is attached to
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields
commerce_percentage_value	decimal(10,2)	Yes	NULL	

field_revision_commerce_price

Table comments: Revision archive storage for field 9 (commerce_price)

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	No		The entity revision id this data is attached to
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields
commerce_price_amount	int(11)	No	0	The price amount.
commerce_price_currency_code	varchar(32)	No		The currency code for the price.
commerce_price_data	longtext	Yes	NULL	A serialized array of additional price data.

field_revision_commerce_product

Table comments: Revision archive storage for field 7 (commerce_product)

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	No		The entity revision id this data is attached to
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields
commerce_product_product_id	int(10)	Yes	NULL	

field_revision_commerce_shipping_service

Table comments: Revision archive storage for field 15 (commerce_shipping...

--	--	--	--	--

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	No		The entity revision id this data is attached to
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields
commerce_shipping_service_value	varchar(255)	Yes	NULL	

field_revision_commerce_total

Table comments: Revision archive storage for field 6 (commerce_total)

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	No		The entity revision id this data is attached to
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields
commerce_total_amount	int(11)	No	0	The price amount.
commerce_total_currency_code	varchar(32)	No		The currency code for the price.
commerce_total_data	longtext	Yes	NULL	A serialized array of additional price data.

field_revision_commerce_unit_price

Table comments: Revision archive storage for field 5 (commerce_unit_price)

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	No		The entity revision id this data is attached to
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields
commerce_unit_price_amount	int(11)	No	0	The price amount.
commerce_unit_price_currency_code	varchar(32)	No		The currency code for the price.
commerce_unit_price_data	longtext	Yes	NULL	A serialized array of additional price data.

field_revision_field_bag_size

Table comments: Revision archive storage for field 31 (field_bag_size)

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	No		The entity revision id this data is attached to

language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields
field_bag_size_tid	int(10)	Yes	NULL	

field_revision_field_blog_category

Table comments: Revision archive storage for field 25 (field_blog_category)

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	No		The entity revision id this data is attached to
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields
field_blog_category_tid	int(10)	Yes	NULL	

field_revision_field_brand

Table comments: Revision archive storage for field 38 (field_brand)

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	No		The entity revision id this data is attached to
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields
field_brand_tid	int(10)	Yes	NULL	

field_revision_field_category

Table comments: Revision archive storage for field 39 (field_category)

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	No		The entity revision id this data is attached to
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields
field_category_tid	int(10)	Yes	NULL	

field_revision_field_category_color

Table comments: Revision archive storage for field 43 (field_category_color)

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	No		The entity revision id this data is attached to
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value

				fields
field_category_color_value	varchar(7)	Yes	NULL	
field_category_color_format	varchar(255)	Yes	NULL	

field_revision_field_collection

Table comments: Revision archive storage for field 40 (field_collection)

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	No		The entity revision id this data is attached to
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields
field_collection_tid	int(10)	Yes	NULL	

field_revision_field_color

Table comments: Revision archive storage for field 32 (field_color)

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	No		The entity revision id this data is attached to
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields
field_color_tid	int(10)	Yes	NULL	

field_revision_field_gender

Table comments: Revision archive storage for field 41 (field_gender)

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	No		The entity revision id this data is attached to
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields
field_gender_tid	int(10)	Yes	NULL	

field_revision_field_hat_size

Table comments: Revision archive storage for field 34 (field_hat_size)

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	No		The entity revision id this data is attached to
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields

field_hat_size_tid	int(10)	Yes	NULL	
--------------------	---------	-----	------	--

field_revision_field_headline

Table comments: Revision archive storage for field 44 (field_headline)

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	No		The entity revision id this data is attached to
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields
field_headline_value	varchar(20)	Yes	NULL	
field_headline_format	varchar(255)	Yes	NULL	

field_revision_field_image

Table comments: Revision archive storage for field 26 (field_image)

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	No		The entity revision id this data is attached to
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields
field_image_fid	int(10)	Yes	NULL	The file_managed.fid being referenced in this field.
field_image_alt	varchar(512)	Yes	NULL	Alternative image text, for the image's 'alt' attribute.
field_image_title	varchar(1024)	Yes	NULL	Image title text, for the image's 'title' attribute.
field_image_width	int(10)	Yes	NULL	The width of the image in pixels.
field_image_height	int(10)	Yes	NULL	The height of the image in pixels.

field_revision_field_images

Table comments: Revision archive storage for field 33 (field_images)

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	No		The entity revision id this data is attached to
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields
field_images_fid	int(10)	Yes	NULL	The file_managed.fid being referenced in this field.
field_images_alt	varchar(512)	Yes	NULL	Alternative image text, for the image's 'alt' attribute.
field_images_title	varchar(1024)	Yes	NULL	Image title text, for the image's 'title' attribute.
field_images_width	int(10)	Yes	NULL	The width of the image in pixels.
field_images_height	int(10)	Yes	NULL	The height of the image in pixels.

field_revision_field_link

Table comments: Revision archive storage for field 29 (field_link)

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to

bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	No		The entity revision id this data is attached to
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields
field_link_url	varchar(2048)	Yes	NULL	
field_link_title	varchar(255)	Yes	NULL	
field_link_attributes	mediumtext	Yes	NULL	

field_revision_field_product

Table comments: Revision archive storage for field 42 (field_product)

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	No		The entity revision id this data is attached to
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields
field_product_product_id	int(10)	Yes	NULL	

field_revision_field_shoe_size

Table comments: Revision archive storage for field 35 (field_shoe_size)

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	No		The entity revision id this data is attached to
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields
field_shoe_size_tid	int(10)	Yes	NULL	

field_revision_field_storage_capacity

Table comments: Revision archive storage for field 36 (field_storage...

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	No		The entity revision id this data is attached to
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields
field_storage_capacity_tid	int(10)	Yes	NULL	

field_revision_field_tagline

Table comments: Revision archive storage for field 30 (field_tagline)

Column	Type	Null	Default	Comments

entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	No		The entity revision id this data is attached to
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields
field_tagline_value	varchar(80)	Yes	NULL	
field_tagline_format	varchar(255)	Yes	NULL	

field_revision_field_tags

Table comments: Revision archive storage for field 27 (field_tags)

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	No		The entity revision id this data is attached to
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields
field_tags_tid	int(10)	Yes	NULL	

field_revision_field_top_size

Table comments: Revision archive storage for field 37 (field_top_size)

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	No		The entity revision id this data is attached to
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields
field_top_size_tid	int(10)	Yes	NULL	

field_revision_message_commerce_body

Table comments: Revision archive storage for field 24 (message_commerce...

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	No		The entity revision id this data is attached to
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields
message_commerce_body_value	longtext	Yes	NULL	
message_commerce_body_format	varchar(255)	Yes	NULL	

field_revision_message_commerce_line_item

Table comments: Revision archive storage for field 22 (message_commerce...

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	No		The entity revision id this data is attached to
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields
message_commerce_line_item_target_id	int(10)	No		The id of the target entity.

field_revision_message_commerce_order

Table comments: Revision archive storage for field 21 (message_commerce...

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	No		The entity revision id this data is attached to
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields
message_commerce_order_target_id	int(10)	No		The id of the target entity.

field_revision_message_commerce_payment

Table comments: Revision archive storage for field 23 (message_commerce...

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	No		The entity revision id this data is attached to
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields
message_commerce_payment_target_id	int(10)	No		The id of the target entity.

field_revision_message_order_display_name

Table comments: Revision archive storage for field 18 (message_order...

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	No		The entity revision id this data is attached to
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields
message_order_display_name_value	varchar(255)	Yes	NULL	

message_order_display_name_format	varchar(255)	Yes	NULL	
-----------------------------------	--------------	-----	------	--

field_revision_message_text

Table comments: Revision archive storage for field 17 (message_text)

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	No		The entity revision id this data is attached to
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields
message_text_value	longtext	Yes	NULL	
message_text_format	varchar(255)	Yes	NULL	

field_revision_title_field

Table comments: Revision archive storage for field 28 (title_field)

Column	Type	Null	Default	Comments
entity_type	varchar(128)	No		The entity type this data is attached to
bundle	varchar(128)	No		The field instance bundle to which this row belongs, used when deleting a field instance
deleted	tinyint(4)	No	0	A boolean indicating whether this data item has been deleted
entity_id	int(10)	No		The entity id this data is attached to
revision_id	int(10)	No		The entity revision id this data is attached to
language	varchar(32)	No		The language for this data item.
delta	int(10)	No		The sequence number for this data item, used for multi-value fields
title_field_value	varchar(255)	Yes	NULL	
title_field_format	varchar(255)	Yes	NULL	

file_managed

Table comments: Stores information for uploaded files.

Column	Type	Null	Default	Comments
fid	int(10)	No		File ID.
uid	int(10)	No	0	The users.uid of the user who is associated with the file.
filename	varchar(255)	No		Name of the file with no path components. This may differ from the basename of the URI if the file is renamed to avoid overwriting an existing file.
uri	varchar(255)	No		The URI to access the file (either local or remote).
filemime	varchar(255)	No		The file's MIME type.
filesize	int(10)	No	0	The size of the file in bytes.
status	tinyint(4)	No	0	A field indicating the status of the file. Two status are defined in core: temporary (0) and permanent (1). Temporary files older than DRUPAL_MAXIMUM_TEMP_FILE_AGE will be removed during a cron run.
timestamp	int(10)	No	0	UNIX timestamp for when the file was added.

file_usage

Table comments: Track where a file is used.

Column	Type	Null	Default	Comments
fid	int(10)	No		File ID.
module	varchar(255)	No		The name of the module that is using the file.
type	varchar(64)	No		The name of the object type in which the file is used.
id	int(10)	No	0	The primary key of the object using the file.
count	int(10)	No	0	The number of times this file is used by this object.

filter

Table comments: Table that maps filters (HTML corrector) to text formats ...

Column	Type	Null	Default	Comments
format	varchar(255)	No		Foreign key: The filter_format.format to which this filter is assigned.
module	varchar(64)	No		The origin module of the filter.
name	varchar(32)	No		Name of the filter being referenced.
weight	int(11)	No	0	Weight of filter within format.
status	int(11)	No	0	Filter enabled status. (1 = enabled, 0 = disabled)
settings	longblob	Yes	NULL	A serialized array of name value pairs that store the filter settings for the specific format.

filter_format

Table comments: Stores text formats: custom groupings of filters, such as...

Column	Type	Null	Default	Comments
format	varchar(255)	No		Primary Key: Unique machine name of the format.
name	varchar(255)	No		Name of the text format (Filtered HTML).
cache	tinyint(4)	No	0	Flag to indicate whether format is cacheable. (1 = cacheable, 0 = not cacheable)
status	tinyint(3)	No	1	The status of the text format. (1 = enabled, 0 = disabled)
weight	int(11)	No	0	Weight of text format to use when listing.

flood

Table comments: Flood controls the threshold of events, such as the...

Column	Type	Null	Default	Comments
fid	int(11)	No		Unique flood event ID.
event	varchar(64)	No		Name of event (e.g. contact).
identifier	varchar(128)	No		Identifier of the visitor, such as an IP address or hostname.
timestamp	int(11)	No	0	Timestamp of the event.
expiration	int(11)	No	0	Expiration timestamp. Expired events are purged on cron run.

history

Table comments: A record of which users have read which nodes.

Column	Type	Null	Default	Comments
uid	int(11)	No	0	The users.uid that read the node nid.
nid	int(11)	No	0	The node.nid that was read.
timestamp	int(11)	No	0	The Unix timestamp at which the read occurred.

image_effects

Table comments: Stores configuration options for image effects.

Column	Type	Null	Default	Comments
ieid	int(10)	No		The primary identifier for an image effect.
isid	int(10)	No	0	The image_styles.isid for an image style.
weight	int(11)	No	0	The weight of the effect in the style.
name	varchar(255)	No		The unique name of the effect to be executed.
data	longblob	No		The configuration data for the effect.

image_styles

Table comments: Stores configuration options for image styles.

Column	Type	Null	Default	Comments
isid	int(10)	No		The primary identifier for an image style.
name	varchar(255)	No		The style name.

menu_custom

Table comments: Holds definitions for top-level custom menus (for example...

Column	Type	Null	Default	Comments
menu_name	varchar(32)	No		Primary Key: Unique key for menu. This is used as a block delta so length is 32.
title	varchar(255)	No		Menu title; displayed at top of block.
description	text	Yes	NULL	Menu description.

menu_links

Table comments: Contains the individual links within a menu.

Column	Type	Null	Default	Comments
menu_name	varchar(32)	No		The menu name. All links with the same menu name (such as 'navigation') are part of the same menu.
mlid	int(10)	No		The menu link ID (mlid) is the integer primary key.
plid	int(10)	No	0	The parent link ID (plid) is the mlid of the link above in the hierarchy, or zero if the link is at the top level in its menu.
link_path	varchar(255)	No		The Drupal path or external path this link points to.
router_path	varchar(255)	No		For links corresponding to a Drupal path (external = 0), this connects the link to a menu_router.path for joins.
link_title	varchar(255)	No		The text displayed for the link, which may be modified by a title callback stored in menu_router.
options	blob	Yes	NULL	A serialized array of options to be passed to the url() or l() function, such as a query string or HTML attributes.
module	varchar(255)	No	system	The name of the module that generated this link.
hidden	smallint(6)	No	0	A flag for whether the link should be rendered in menus. (1 = a disabled menu item that may be shown on admin screens, -1 = a menu callback, 0 = a normal, visible link)
external	smallint(6)	No	0	A flag to indicate if the link points to a full URL starting with a protocol, like http:// (1 = external, 0 = internal).
has_children	smallint(6)	No	0	Flag indicating whether any links have this link as a parent (1 = children exist, 0 = no children).
expanded	smallint(6)	No	0	Flag for whether this link should be rendered as expanded in menus - expanded links always have their child links displayed, instead of only when the link is in the active trail (1 = expanded, 0 = not expanded)
weight	int(11)	No	0	Link weight among links in the same menu at the same depth.
depth	smallint(6)	No	0	The depth relative to the top level. A link with plid == 0 will have depth == 1.
customized	smallint(6)	No	0	A flag to indicate that the user has manually created or edited the link (1 = customized, 0 = not customized).
p1	int(10)	No	0	The first mlid in the materialized path. If N = depth, then pN must equal the mlid. If depth > 1 then p(N-1) must equal the plid. All pX where X > depth must equal zero. The columns p1 .. p9 are also called the parents.
p2	int(10)	No	0	The second mlid in the materialized path. See p1.
p3	int(10)	No	0	The third mlid in the materialized path. See p1.
p4	int(10)	No	0	The fourth mlid in the materialized path. See p1.
p5	int(10)	No	0	The fifth mlid in the materialized path. See p1.
p6	int(10)	No	0	The sixth mlid in the materialized path. See p1.
p7	int(10)	No	0	The seventh mlid in the materialized path. See p1.
p8	int(10)	No	0	The eighth mlid in the materialized path. See p1.
p9	int(10)	No	0	The ninth mlid in the materialized path. See p1.
updated	smallint(6)	No	0	Flag that indicates that this link was generated during the update from Drupal 5.

menu_router

Table comments: Maps paths to various callbacks (access, page and title)

Column	Type	Null	Default	Comments
path	varchar(255)	No		Primary Key: the Drupal path this entry describes
load_functions	blob	No		A serialized array of function names (like node_load) to be called to load an object corresponding to a part of the current path.
to_arg_functions	blob	No		A serialized array of function names (like user_uid_optional_to_arg) to

				be called to replace a part of the router path with another string.
access_callback	varchar(255)	No		The callback which determines the access to this router path. Defaults to user_access.
access_arguments	blob	Yes	NULL	A serialized array of arguments for the access callback.
page_callback	varchar(255)	No		The name of the function that renders the page.
page_arguments	blob	Yes	NULL	A serialized array of arguments for the page callback.
delivery_callback	varchar(255)	No		The name of the function that sends the result of the page_callback function to the browser.
fit	int(11)	No	0	A numeric representation of how specific the path is.
number_parts	smallint(6)	No	0	Number of parts in this router path.
context	int(11)	No	0	Only for local tasks (tabs) - the context of a local task to control its placement.
tab_parent	varchar(255)	No		Only for local tasks (tabs) - the router path of the parent page (which may also be a local task).
tab_root	varchar(255)	No		Router path of the closest non-tab parent page. For pages that are not local tasks, this will be the same as the path.
title	varchar(255)	No		The title for the current page, or the title for the tab if this is a local task.
title_callback	varchar(255)	No		A function which will alter the title. Defaults to t()
title_arguments	varchar(255)	No		A serialized array of arguments for the title callback. If empty, the title will be used as the sole argument for the title callback.
theme_callback	varchar(255)	No		A function which returns the name of the theme that will be used to render this page. If left empty, the default theme will be used.
theme_arguments	varchar(255)	No		A serialized array of arguments for the theme callback.
type	int(11)	No	0	Numeric representation of the type of the menu item, like MENU_LOCAL_TASK.
description	text	No		A description of this item.
position	varchar(255)	No		The position of the block (left or right) on the system administration page for this item.
weight	int(11)	No	0	Weight of the element. Lighter weights are higher up, heavier weights go down.
include_file	mediumtext	Yes	NULL	The file to include for this element, usually the page callback function lives in this file.

message

Table comments: An instance of a message type (e.g. like a node is an...

Column	Type	Null	Default	Comments
mid	int(10)	No		The Unique ID of the message.
type	varchar(255)	No		Reference to a message a type.
arguments	text	Yes	NULL	Serialized array with the arguments
uid	int(10)	Yes	NULL	The user ID of the acting user.
timestamp	int(10)	No		When the message instance was recorded.
language	varchar(12)	No		The languages.language of this message.

message_type

Table comments: Storage for user-defined message templates.

Column	Type	Null	Default	Comments
id	int(11)	No		Primary Key: Numeric message type ID.
name	varchar(255)	No		The unified identifier for a message type.
category	varchar(255)	No	message_type	Reference to a message type category.
description	varchar(255)	No		Description for this message type.
argument_keys	text	Yes	NULL	Serialized array with the argument keys
language	varchar(12)	No		The languages.language of this message type.
status	tinyint(4)	No	1	The exportable status of the entity.
module	varchar(255)	Yes	NULL	The name of the providing module if the entity has been defined in code.
arguments	text	Yes	NULL	Serialized array with the arguments.
data	longtext	Yes	NULL	Serialized array with general data.

message_type_category

Table comments: Storage for user-defined message category.

Column	Type	Null	Default	Comments
id	int(11)	No		Primary Key: Numeric message type category ID.
category	varchar(255)	No		The unified identifier for a message type category.
description	varchar(255)	No		Description for this message type category.
language	varchar(12)	No		The languages.language of this message type category.
status	tinyint(4)	No	1	The exportable status of the entity.
module	varchar(255)	Yes	NULL	The name of the providing module if the entity has been defined in code.

migrate_log

Table comments: History of migration processes

Column	Type	Null	Default	Comments
mid	int(10)	No		Primary key for migrate_log table
machine_name	varchar(255)	No		Unique machine name for migration
process_type	tinyint(3)	No		Type of migration process - 1 for import, 2 for rollback
starttime	bigint(20)	No		Begin time of a migration process, times 1000
endtime	bigint(20)	Yes	NULL	End time of a migration process, times 1000
initialhighwater	varchar(255)	No		Initial highwater mark
finalhighwater	varchar(255)	Yes	NULL	Final highwater mark
numprocessed	int(10)	Yes	NULL	Number of items processed

migrate_map_commercekickstartadpush

Table comments: Mappings from source key to destination key

Column	Type	Null	Default	Comments
sourceid1	varchar(255)	No		
destid1	int(10)	Yes	NULL	ID of destination node
needs_update	tinyint(3)	No	0	Indicates current status of the source row
rollback_action	tinyint(3)	No	0	Flag indicating what to do for this item on rollback
last_imported	int(10)	No	0	UNIX timestamp of the last time this row was imported

migrate_map_commercekickstartbagscases

Table comments: Mappings from source key to destination key

Column	Type	Null	Default	Comments
sourceid1	varchar(32)	No		
destid1	int(10)	Yes	NULL	
destid2	int(10)	Yes	NULL	
needs_update	tinyint(3)	No	0	Indicates current status of the source row
rollback_action	tinyint(3)	No	0	Flag indicating what to do for this item on rollback
last_imported	int(10)	No	0	UNIX timestamp of the last time this row was imported

migrate_map_commercekickstartblogpost

Table comments: Mappings from source key to destination key

Column	Type	Null	Default	Comments
sourceid1	varchar(255)	No		
destid1	int(10)	Yes	NULL	ID of destination node
needs_update	tinyint(3)	No	0	Indicates current status of the source row
rollback_action	tinyint(3)	No	0	Flag indicating what to do for this item on rollback
last_imported	int(10)	No	0	UNIX timestamp of the last time this row was imported

migrate_map_commercekickstartcollection

Table comments: Mappings from source key to destination key

Column	Type	Null	Default	Comments
sourceid1	varchar(255)	No		
destid1	int(10)	Yes	NULL	ID of destination term
needs_update	tinyint(3)	No	0	Indicates current status of the source row
rollback_action	tinyint(3)	No	0	Flag indicating what to do for this item on rollback
last_imported	int(10)	No	0	UNIX timestamp of the last time this row was imported

migrate_map_commercekickstartdrinks

Table comments: Mappings from source key to destination key

Column	Type	Null	Default	Comments
sourceid1	varchar(32)	No		
destid1	int(10)	Yes	NULL	
destid2	int(10)	Yes	NULL	
needs_update	tinyint(3)	No	0	Indicates current status of the source row
rollback_action	tinyint(3)	No	0	Flag indicating what to do for this item on rollback
last_imported	int(10)	No	0	UNIX timestamp of the last time this row was imported

migrate_map_commercekickstarthats

Table comments: Mappings from source key to destination key

Column	Type	Null	Default	Comments
sourceid1	varchar(32)	No		
destid1	int(10)	Yes	NULL	
destid2	int(10)	Yes	NULL	
needs_update	tinyint(3)	No	0	Indicates current status of the source row
rollback_action	tinyint(3)	No	0	Flag indicating what to do for this item on rollback
last_imported	int(10)	No	0	UNIX timestamp of the last time this row was imported

migrate_map_commercekickstartnodebags_cases

Table comments: Mappings from source key to destination key

Column	Type	Null	Default	Comments
sourceid1	varchar(255)	No		
destid1	int(10)	Yes	NULL	ID of destination node
needs_update	tinyint(3)	No	0	Indicates current status of the source row
rollback_action	tinyint(3)	No	0	Flag indicating what to do for this item on rollback
last_imported	int(10)	No	0	UNIX timestamp of the last time this row was imported

migrate_map_commercekickstartnodedrinks

Table comments: Mappings from source key to destination key

Column	Type	Null	Default	Comments
sourceid1	varchar(255)	No		
destid1	int(10)	Yes	NULL	ID of destination node
needs_update	tinyint(3)	No	0	Indicates current status of the source row
rollback_action	tinyint(3)	No	0	Flag indicating what to do for this item on rollback
last_imported	int(10)	No	0	UNIX timestamp of the last time this row was imported

migrate_map_commercekickstartnodehats

Table comments: Mappings from source key to destination key

Column	Type	Null	Default	Comments
sourceid1	varchar(255)	No		
destid1	int(10)	Yes	NULL	ID of destination node
needs_update	tinyint(3)	No	0	Indicates current status of the source row

rollback_action	tinyint(3)	No	0	Flag indicating what to do for this item on rollback
last_imported	int(10)	No	0	UNIX timestamp of the last time this row was imported

migrate_map_commercekickstartnodeshoes

Table comments: Mappings from source key to destination key

Column	Type	Null	Default	Comments
sourceid1	varchar(255)	No		
destid1	int(10)	Yes	NULL	ID of destination node
needs_update	tinyint(3)	No	0	Indicates current status of the source row
rollback_action	tinyint(3)	No	0	Flag indicating what to do for this item on rollback
last_imported	int(10)	No	0	UNIX timestamp of the last time this row was imported

migrate_map_commercekickstartnodestorage_devices

Table comments: Mappings from source key to destination key

Column	Type	Null	Default	Comments
sourceid1	varchar(255)	No		
destid1	int(10)	Yes	NULL	ID of destination node
needs_update	tinyint(3)	No	0	Indicates current status of the source row
rollback_action	tinyint(3)	No	0	Flag indicating what to do for this item on rollback
last_imported	int(10)	No	0	UNIX timestamp of the last time this row was imported

migrate_map_commercekickstartnodetops

Table comments: Mappings from source key to destination key

Column	Type	Null	Default	Comments
sourceid1	varchar(255)	No		
destid1	int(10)	Yes	NULL	ID of destination node
needs_update	tinyint(3)	No	0	Indicates current status of the source row
rollback_action	tinyint(3)	No	0	Flag indicating what to do for this item on rollback
last_imported	int(10)	No	0	UNIX timestamp of the last time this row was imported

migrate_map_commercekickstartpages

Table comments: Mappings from source key to destination key

Column	Type	Null	Default	Comments
sourceid1	varchar(255)	No		
destid1	int(10)	Yes	NULL	ID of destination node
needs_update	tinyint(3)	No	0	Indicates current status of the source row
rollback_action	tinyint(3)	No	0	Flag indicating what to do for this item on rollback
last_imported	int(10)	No	0	UNIX timestamp of the last time this row was imported

migrate_map_commercekickstartshoes

Table comments: Mappings from source key to destination key

Column	Type	Null	Default	Comments
sourceid1	varchar(32)	No		
destid1	int(10)	Yes	NULL	
destid2	int(10)	Yes	NULL	
needs_update	tinyint(3)	No	0	Indicates current status of the source row
rollback_action	tinyint(3)	No	0	Flag indicating what to do for this item on rollback
last_imported	int(10)	No	0	UNIX timestamp of the last time this row was imported

migrate_map_commercekickstartslideshow

Table comments: Mappings from source key to destination key

Column	Type	Null	Default	Comments
--------	------	------	---------	----------

sourceid1	varchar(255)	No		
destid1	int(10)	Yes	NULL	ID of destination node
needs_update	tinyint(3)	No	0	Indicates current status of the source row
rollback_action	tinyint(3)	No	0	Flag indicating what to do for this item on rollback
last_imported	int(10)	No	0	UNIX timestamp of the last time this row was imported

migrate_map_commercekickstartstorage

Table comments: Mappings from source key to destination key

Column	Type	Null	Default	Comments
sourceid1	varchar(32)	No		
destid1	int(10)	Yes	NULL	
destid2	int(10)	Yes	NULL	
needs_update	tinyint(3)	No	0	Indicates current status of the source row
rollback_action	tinyint(3)	No	0	Flag indicating what to do for this item on rollback
last_imported	int(10)	No	0	UNIX timestamp of the last time this row was imported

migrate_map_commercekickstarttops

Table comments: Mappings from source key to destination key

Column	Type	Null	Default	Comments
sourceid1	varchar(32)	No		
destid1	int(10)	Yes	NULL	
destid2	int(10)	Yes	NULL	
needs_update	tinyint(3)	No	0	Indicates current status of the source row
rollback_action	tinyint(3)	No	0	Flag indicating what to do for this item on rollback
last_imported	int(10)	No	0	UNIX timestamp of the last time this row was imported

migrate_message_commercekickstartadpush

Table comments: Messages generated during a migration process

Column	Type	Null	Default	Comments
msgid	int(10)	No		
sourceid1	varchar(255)	No		
level	int(10)	No	1	
message	mediumtext	No		

migrate_message_commercekickstartbagscases

Table comments: Messages generated during a migration process

Column	Type	Null	Default	Comments
msgid	int(10)	No		
sourceid1	varchar(32)	No		
level	int(10)	No	1	
message	mediumtext	No		

migrate_message_commercekickstartblogpost

Table comments: Messages generated during a migration process

Column	Type	Null	Default	Comments
msgid	int(10)	No		
sourceid1	varchar(255)	No		
level	int(10)	No	1	
message	mediumtext	No		

migrate_message_commercekickstartcollection

Table comments: Messages generated during a migration process

Column	Type	Null	Default	Comments
msgid	int(10)	No		
sourceid1	varchar(255)	No		
level	int(10)	No	1	
message	mediumtext	No		

migrate_message_commercekickstartdrinks

Table comments: Messages generated during a migration process

Column	Type	Null	Default	Comments
msgid	int(10)	No		
sourceid1	varchar(32)	No		
level	int(10)	No	1	
message	mediumtext	No		

migrate_message_commercekickstarthats

Table comments: Messages generated during a migration process

Column	Type	Null	Default	Comments
msgid	int(10)	No		
sourceid1	varchar(32)	No		
level	int(10)	No	1	
message	mediumtext	No		

migrate_message_commercekickstartnodebags_cases

Table comments: Messages generated during a migration process

Column	Type	Null	Default	Comments
msgid	int(10)	No		
sourceid1	varchar(255)	No		
level	int(10)	No	1	
message	mediumtext	No		

migrate_message_commercekickstartnodedrinks

Table comments: Messages generated during a migration process

Column	Type	Null	Default	Comments
msgid	int(10)	No		
sourceid1	varchar(255)	No		
level	int(10)	No	1	
message	mediumtext	No		

migrate_message_commercekickstartnodehats

Table comments: Messages generated during a migration process

Column	Type	Null	Default	Comments
msgid	int(10)	No		
sourceid1	varchar(255)	No		
level	int(10)	No	1	
message	mediumtext	No		

migrate_message_commercekickstartnodeshoes

Table comments: Messages generated during a migration process

Column	Type	Null	Default	Comments
msgid	int(10)	No		

sourceid1	varchar(255)	No		
level	int(10)	No	1	
message	mediumtext	No		

migrate_message_commercekickstartnodestorage_devices

Table comments: Messages generated during a migration process

Column	Type	Null	Default	Comments
msgid	int(10)	No		
sourceid1	varchar(255)	No		
level	int(10)	No	1	
message	mediumtext	No		

migrate_message_commercekickstartnodetops

Table comments: Messages generated during a migration process

Column	Type	Null	Default	Comments
msgid	int(10)	No		
sourceid1	varchar(255)	No		
level	int(10)	No	1	
message	mediumtext	No		

migrate_message_commercekickstartpages

Table comments: Messages generated during a migration process

Column	Type	Null	Default	Comments
msgid	int(10)	No		
sourceid1	varchar(255)	No		
level	int(10)	No	1	
message	mediumtext	No		

migrate_message_commercekickstartshoes

Table comments: Messages generated during a migration process

Column	Type	Null	Default	Comments
msgid	int(10)	No		
sourceid1	varchar(32)	No		
level	int(10)	No	1	
message	mediumtext	No		

migrate_message_commercekickstartslideshow

Table comments: Messages generated during a migration process

Column	Type	Null	Default	Comments
msgid	int(10)	No		
sourceid1	varchar(255)	No		
level	int(10)	No	1	
message	mediumtext	No		

migrate_message_commercekickstartstorage

Table comments: Messages generated during a migration process

Column	Type	Null	Default	Comments
msgid	int(10)	No		
sourceid1	varchar(32)	No		
level	int(10)	No	1	
message	mediumtext	No		

migrate_message_commercekickstarttops

Table comments: Messages generated during a migration process

Column	Type	Null	Default	Comments
msgid	int(10)	No		
sourceid1	varchar(32)	No		
level	int(10)	No	1	
message	mediumtext	No		

migrate_status

Table comments: Status information for migrations

Column	Type	Null	Default	Comments
machine_name	varchar(255)	No		Unique machine name for migration
class_name	varchar(255)	No		Name of class to instantiate for this migration
status	tinyint(3)	No	0	Current status of migration
highwater	varchar(255)	No		Highwater mark for detecting updated content
arguments	longblob	Yes	NULL	A serialized array of arguments to the migration constructor

node

Table comments: The base table for nodes.

Column	Type	Null	Default	Comments
nid	int(10)	No		The primary identifier for a node.
vid	int(10)	Yes	NULL	The current node_revision.vid version identifier.
type	varchar(32)	No		The node_type.type of this node.
language	varchar(12)	No		The languages.language of this node.
title	varchar(255)	No		The title of this node, always treated as non-markup plain text.
uid	int(11)	No	0	The users.uid that owns this node; initially, this is the user that created it.
status	int(11)	No	1	Boolean indicating whether the node is published (visible to non-administrators).
created	int(11)	No	0	The Unix timestamp when the node was created.
changed	int(11)	No	0	The Unix timestamp when the node was most recently saved.
comment	int(11)	No	0	Whether comments are allowed on this node: 0 = no, 1 = closed (read only), 2 = open (read/write).
promote	int(11)	No	0	Boolean indicating whether the node should be displayed on the front page.
sticky	int(11)	No	0	Boolean indicating whether the node should be displayed at the top of lists in which it appears.
tnid	int(10)	No	0	The translation set id for this node, which equals the node id of the source post in each set.
translate	int(11)	No	0	A boolean indicating whether this translation page needs to be updated.

node_access

Table comments: Identifies which realm/grant pairs a user must possess in...

Column	Type	Null	Default	Comments
nid	int(10)	No	0	The node.nid this record affects.
gid	int(10)	No	0	The grant ID a user must possess in the specified realm to gain this row's privileges on the node.
realm	varchar(255)	No		The realm in which the user must possess the grant ID. Each node access node can define one or more realms.
grant_view	tinyint(3)	No	0	Boolean indicating whether a user with the realm/grant pair can view this node.
grant_update	tinyint(3)	No	0	Boolean indicating whether a user with the realm/grant pair can edit this node.
grant_delete	tinyint(3)	No	0	Boolean indicating whether a user with the realm/grant pair can delete this node.

node_comment_statistics

Table comments: Maintains statistics of node and comments posts to show ...

Column	Type	Null	Default	Comments
nid	int(10)	No	0	The node.nid for which the statistics are compiled.
cid	int(11)	No	0	The comment.cid of the last comment.
last_comment_timestamp	int(11)	No	0	The Unix timestamp of the last comment that was posted within this node, from comment.changed.
last_comment_name	varchar(60)	Yes	NULL	The name of the latest author to post a comment on this node, from comment.name.
last_comment_uid	int(11)	No	0	The user ID of the latest author to post a comment on this node, from comment.uid.
comment_count	int(10)	No	0	The total number of comments on this node.

node_revision

Table comments: Stores information about each saved version of a node.

Column	Type	Null	Default	Comments
nid	int(10)	No	0	The node this version belongs to.
vid	int(10)	No		The primary identifier for this version.
uid	int(11)	No	0	The users.uid that created this version.
title	varchar(255)	No		The title of this version.
log	longtext	No		The log entry explaining the changes in this version.
timestamp	int(11)	No	0	A Unix timestamp indicating when this version was created.
status	int(11)	No	1	Boolean indicating whether the node (at the time of this revision) is published (visible to non-administrators).
comment	int(11)	No	0	Whether comments are allowed on this node (at the time of this revision): 0 = no, 1 = closed (read only), 2 = open (read/write).
promote	int(11)	No	0	Boolean indicating whether the node (at the time of this revision) should be displayed on the front page.
sticky	int(11)	No	0	Boolean indicating whether the node (at the time of this revision) should be displayed at the top of lists in which it appears.

node_type

Table comments: Stores information about all defined node types.

Column	Type	Null	Default	Comments
type	varchar(32)	No		The machine-readable name of this type.
name	varchar(255)	No		The human-readable name of this type.
base	varchar(255)	No		The base string used to construct callbacks corresponding to this node type.
module	varchar(255)	No		The module defining this node type.
description	mediumtext	No		A brief description of this type.
help	mediumtext	No		Help information shown to the user when creating a node of this type.
has_title	tinyint(3)	No		Boolean indicating whether this type uses the node.title field.
title_label	varchar(255)	No		The label displayed for the title field on the edit form.
custom	tinyint(4)	No	0	A boolean indicating whether this type is defined by a module (FALSE) or by a user via Add content type (TRUE).
modified	tinyint(4)	No	0	A boolean indicating whether this type has been modified by an administrator; currently not used in any way.
locked	tinyint(4)	No	0	A boolean indicating whether the administrator can change the machine name of this type.
disabled	tinyint(4)	No	0	A boolean indicating whether the node type is disabled.
orig_type	varchar(255)	No		The original machine-readable name of this node type. This may be different from the current type name if the locked field is 0.

oauth_common_consumer

Table comments: Keys and secrets for OAuth consumers, both those provided...

Column	Type	Null	Default	Comments
csid	int(11)	No		Primary ID field for the table. Not used for anything except internal lookups.
key_hash	char(40)	No		SHA1-hash of consumer_key.

consumer_key	text	No		Consumer key.
secret	text	No		Consumer secret.
configuration	longtext	No		Consumer configuration

oauth_common_context

Table comments: Stores contexts for OAuth common

Column	Type	Null	Default	Comments
cid	int(11)	No		Primary ID field for the table. Not used for anything except internal lookups.
name	varchar(32)	No		The computer-readable name of the context.
title	varchar(100)	No		The localizable title of the authorization context.
authorization_options	longtext	No		Authorization options.
authorization_levels	longtext	No		Authorization levels for the context.

oauth_common_nonce

Table comments: Stores timestamp against nonce for repeat attacks.

Column	Type	Null	Default	Comments
nonce	varchar(255)	No		The random string used on each request.
timestamp	int(11)	No		The timestamp of the request.
token_key	varchar(32)	No		Token key.

oauth_common_provider_consumer

Table comments: Additional data for OAuth consumers provided by this site.

Column	Type	Null	Default	Comments
csid	int(10)	Yes	0	The oauth_common_consumer.csid this data is related to.
consumer_key	char(32)	No		Consumer key.
created	int(11)	No	0	The time that the consumer was created, as a Unix timestamp.
changed	int(11)	No	0	The last time the consumer was edited, as a Unix timestamp.
uid	int(10)	No		The application owner.
name	varchar(128)	No		The application name.
context	varchar(32)	No		The application context.
callback_url	varchar(255)	No		Callback url.

oauth_common_provider_token

Table comments: Additional data for OAuth tokens provided by this site.

Column	Type	Null	Default	Comments
tid	int(10)	Yes	0	The oauth_common_token.tid this data is related to.
token_key	char(32)	No		Token key.
created	int(11)	No	0	The time that the token was created, as a Unix timestamp.
changed	int(11)	No	0	The last time the token was edited, as a Unix timestamp.
services	text	Yes	NULL	An array of services that the user allowed the consumer to access.
authorized	tinyint(4)	No	0	In case its a request token, it checks if the user already authorized the consumer to get an access token.

oauth_common_token

Table comments: Tokens stored on behalf of providers or consumers for...

Column	Type	Null	Default	Comments
tid	int(11)	No		Primary ID field for the table. Not used for anything except internal lookups.
csid	int(10)	No	0	The oauth_common_consumer.csid this token is related to.
key_hash	char(40)	No		SHA1-hash of token_key.
token_key	text	No		Token key.
secret	text	No		Token secret.

expires	int(11)	No	0	The expiry time for the token, as a Unix timestamp.
type	tinyint(4)	No	1	Token type: request or access.
uid	int(10)	No	0	User ID from user.uid.

oauthconnector_connections

Table comments: Stores information about connections between OAuth tokens...

Column	Type	Null	Default	Comments
tid	int(10)	No	0	The oauth_common_token.tid this connection is related to.
cid	varchar(255)	No		The external id of a connection.

oauthconnector_fields

Table comments: Stores information about fields definition.

Column	Type	Null	Default	Comments
name	varchar(32)	No		The system name.
title	varchar(255)	No		The title of the field.
description	varchar(255)	Yes	NULL	The description for the field.
required	int(10)	Yes	0	Is this field required

oauthconnector_provider

Table comments: Stores information about OAuth providers.

Column	Type	Null	Default	Comments
pid	int(10)	No		The primary identifier for a provider.
name	varchar(100)	No		The machine-readable name of the provider.
title	varchar(255)	No		The human-readable title of the provider.
url	varchar(255)	No		A URL to the OAuth provider, typically to the front page.
csid	int(10)	No	0	The oauth_common_consumer.csid of the OAuth consumer to use.
consumer_advanced	longtext	No		Serialized advanced settings for an oauth consumer, like signature method.
mapping	longtext	No		Serialized mapping between the response of the API and Connector properties.

queue

Table comments: Stores items in queues.

Column	Type	Null	Default	Comments
item_id	int(10)	No		Primary Key: Unique item ID.
name	varchar(255)	No		The queue name.
data	longblob	Yes	NULL	The arbitrary data for the item.
expire	int(11)	No	0	Timestamp when the claim lease expires on the item.
created	int(11)	No	0	Timestamp when the item was created.

registry

Table comments: Each record is a function, class, or interface name and...

Column	Type	Null	Default	Comments
name	varchar(255)	No		The name of the function, class, or interface.
type	varchar(9)	No		Either function or class or interface.
filename	varchar(255)	No		Name of the file.
module	varchar(255)	No		Name of the module the file belongs to.
weight	int(11)	No	0	The order in which this module's hooks should be invoked relative to other modules. Equal-weighted modules are ordered by name.

registry_file

Table comments: Files parsed to build the registry.

--	--	--	--	--

Column	Type	Null	Default	Comments
filename	varchar(255)	No		Path to the file.
hash	varchar(64)	No		sha-256 hash of the file's contents when last parsed.

role

Table comments: Stores user roles.

Column	Type	Null	Default	Comments
rid	int(10)	No		Primary Key: Unique role ID.
name	varchar(64)	No		Unique role name.
weight	int(11)	No	0	The weight of this role in listings and the user interface.

role_permission

Table comments: Stores the permissions assigned to user roles.

Column	Type	Null	Default	Comments
rid	int(10)	No		Foreign Key: role.rid.
permission	varchar(128)	No		A single permission granted to the role identified by rid.
module	varchar(255)	No		The module declaring the permission.

rules_config

Table comments: rules_config

Column	Type	Null	Default	Comments
id	int(11)	No		The internal identifier for any configuration.
name	varchar(64)	No		The name of the configuration.
label	varchar(255)	No	unlabeled	The label of the configuration.
plugin	varchar(127)	No		The name of the plugin of this configuration.
active	int(11)	No	1	Boolean indicating whether the configuration is active. Usage depends on how the using module makes use of it.
weight	tinyint(4)	No	0	Weight of the configuration. Usage depends on how the using module makes use of it.
status	tinyint(4)	No	1	The exportable status of the entity.
dirty	tinyint(4)	No	0	Dirty configurations fail the integrity check, e.g. due to missing dependencies.
module	varchar(255)	Yes	NULL	The name of the providing module if the entity has been defined in code.
access_exposed	tinyint(4)	No	0	Whether to use a permission to control access for using components.
data	longblob	Yes	NULL	Everything else, serialized.

rules_dependencies

Table comments: rules_dependencies

Column	Type	Null	Default	Comments
id	int(10)	No		The primary identifier of the configuration.
module	varchar(255)	No		The name of the module that is required for the configuration.

rules_tags

Table comments: rules_tags

Column	Type	Null	Default	Comments
id	int(10)	No		The primary identifier of the configuration.
tag	varchar(255)	No		The tag string associated with this configuration

rules_trigger

Table comments: rules_trigger

Column	Type	Null	Default	Comments
id	int(10)	No		The primary identifier of the configuration.

event	varchar(127)	No		The name of the event on which the configuration should be triggered.
-------	--------------	----	--	---

search_api_db_product_display_changed

Table comments: search_api_db_product_display_changed

Column	Type	Null	Default	Comments
item_id	int(11)	No		The primary identifier of the item.
value	int(11)	Yes	NULL	The field's value for this item.

search_api_db_product_display_created

Table comments: search_api_db_product_display_created

Column	Type	Null	Default	Comments
item_id	int(11)	No		The primary identifier of the item.
value	int(11)	Yes	NULL	The field's value for this item.

search_api_db_product_display_field_blog_category

Table comments: search_api_db_product_display_field_blog_category

Column	Type	Null	Default	Comments
item_id	int(11)	No		The primary identifier of the item.
value	int(11)	No		The field's value for this item.

search_api_db_product_display_field_blog_category_name

Table comments: search_api_db_product_display_field_blog_category_name

Column	Type	Null	Default	Comments
item_id	int(11)	No		The primary identifier of the item.
value	varchar(255)	No		The field's value for this item.

search_api_db_product_display_field_brand

Table comments: search_api_db_product_display_field_brand

Column	Type	Null	Default	Comments
item_id	int(11)	No		The primary identifier of the item.
value	int(11)	Yes	NULL	The field's value for this item.

search_api_db_product_display_field_brand_name

Table comments: search_api_db_product_display_field_brand_name

Column	Type	Null	Default	Comments
item_id	int(11)	No		The primary identifier of the item.
value	varchar(255)	Yes	NULL	The field's value for this item.

search_api_db_product_display_field_category

Table comments: search_api_db_product_display_field_category

Column	Type	Null	Default	Comments
item_id	int(11)	No		The primary identifier of the item.
value	int(11)	Yes	NULL	The field's value for this item.

search_api_db_product_display_field_category_name

Table comments: search_api_db_product_display_field_category_name

Column	Type	Null	Default	Comments
item_id	int(11)	No		The primary identifier of the item.
value	varchar(255)	Yes	NULL	The field's value for this item.

search_api_db_product_display_field_collection

Table comments: search_api_db_product_display_field_collection

Column	Type	Null	Default	Comments
item_id	int(11)	No		The primary identifier of the item.
value	int(11)	Yes	NULL	The field's value for this item.

search_api_db_product_display_field_collection_name

Table comments: search_api_db_product_display_field_collection_name

Column	Type	Null	Default	Comments
item_id	int(11)	No		The primary identifier of the item.
value	varchar(255)	Yes	NULL	The field's value for this item.

search_api_db_product_display_field_gender

Table comments: search_api_db_product_display_field_gender

Column	Type	Null	Default	Comments
item_id	int(11)	No		The primary identifier of the item.
value	int(11)	Yes	NULL	The field's value for this item.

search_api_db_product_display_field_gender_name

Table comments: search_api_db_product_display_field_gender_name

Column	Type	Null	Default	Comments
item_id	int(11)	No		The primary identifier of the item.
value	varchar(255)	Yes	NULL	The field's value for this item.

search_api_db_product_display_field_product

Table comments: search_api_db_product_display_field_product

Column	Type	Null	Default	Comments
item_id	int(11)	No		The primary identifier of the item.
value	int(11)	No		The field's value for this item.

search_api_db_product_display_field_product_commerce_price_am_1

Table comments: search_api_db_product_display_field_product_commerce_price_am_1

Column	Type	Null	Default	Comments
item_id	int(11)	No		The primary identifier of the item.
value	float	Yes	NULL	The field's value for this item.

search_api_db_product_display_field_product_commerce_price_am_2

Table comments: search_api_db_product_display_field_product_commerce_price_am_2

Column	Type	Null	Default	Comments
item_id	int(11)	No		The primary identifier of the item.
value	float	No		The field's value for this item.

search_api_db_product_display_field_product_commerce_price_amou

Table comments: search_api_db_product_display_field_product_commerce_price_amou

Column	Type	Null	Default	Comments
item_id	int(11)	No		The primary identifier of the item.
value	float	Yes	NULL	The field's value for this item.

search_api_db_product_display_field_product_field_bag_size

Table comments: search_api_db_product_display_field_product_field_bag_size

Column	Type	Null	Default	Comments
item_id	int(11)	No		The primary identifier of the item.
value	int(11)	No		The field's value for this item.

search_api_db_product_display_field_product_field_bag_size_name

Table comments: search_api_db_product_display_field_product_field_bag_size_name

Column	Type	Null	Default	Comments
item_id	int(11)	No		The primary identifier of the item.
value	varchar(255)	No		The field's value for this item.

search_api_db_product_display_field_product_field_color

Table comments: search_api_db_product_display_field_product_field_color

Column	Type	Null	Default	Comments
item_id	int(11)	No		The primary identifier of the item.
value	int(11)	No		The field's value for this item.

search_api_db_product_display_field_product_field_color_name

Table comments: search_api_db_product_display_field_product_field_color_name

Column	Type	Null	Default	Comments
item_id	int(11)	No		The primary identifier of the item.
value	varchar(255)	No		The field's value for this item.

search_api_db_product_display_field_product_field_hat_size

Table comments: search_api_db_product_display_field_product_field_hat_size

Column	Type	Null	Default	Comments
item_id	int(11)	No		The primary identifier of the item.
value	int(11)	No		The field's value for this item.

search_api_db_product_display_field_product_field_hat_size_name

Table comments: search_api_db_product_display_field_product_field_hat_size_name

Column	Type	Null	Default	Comments
item_id	int(11)	No		The primary identifier of the item.
value	varchar(255)	No		The field's value for this item.

search_api_db_product_display_field_product_field_shoe_size

Table comments: search_api_db_product_display_field_product_field_shoe_size

Column	Type	Null	Default	Comments
item_id	int(11)	No		The primary identifier of the item.
value	int(11)	No		The field's value for this item.

search_api_db_product_display_field_product_field_shoe_size_nam

Table comments: search_api_db_product_display_field_product_field_shoe_size_nam

Column	Type	Null	Default	Comments
item_id	int(11)	No		The primary identifier of the item.
value	varchar(255)	No		The field's value for this item.

search_api_db_product_display_field_product_field_storage_cap_1

Table comments: search_api_db_product_display_field_product_field_storage_cap_1

Column	Type	Null	Default	Comments
--------	------	------	---------	----------

Column	Type	Null	Default	Comments
item_id	int(11)	No		The primary identifier of the item.
value	varchar(255)	No		The field's value for this item.

search_api_db_product_display_field_product_field_storage_capac

Table comments: search_api_db_product_display_field_product_field_storage_capac

Column	Type	Null	Default	Comments
item_id	int(11)	No		The primary identifier of the item.
value	int(11)	No		The field's value for this item.

search_api_db_product_display_field_product_field_top_size

Table comments: search_api_db_product_display_field_product_field_top_size

Column	Type	Null	Default	Comments
item_id	int(11)	No		The primary identifier of the item.
value	int(11)	No		The field's value for this item.

search_api_db_product_display_field_product_field_top_size_name

Table comments: search_api_db_product_display_field_product_field_top_size_name

Column	Type	Null	Default	Comments
item_id	int(11)	No		The primary identifier of the item.
value	varchar(255)	No		The field's value for this item.

search_api_db_product_display_field_tags

Column	Type	Null	Default	Comments
item_id	int(11)	No		The primary identifier of the item.
value	int(11)	No		The field's value for this item.

search_api_db_product_display_field_tags_name

Column	Type	Null	Default	Comments
item_id	int(11)	No		The primary identifier of the item.
value	varchar(255)	No		The field's value for this item.

search_api_db_product_display_nid

Column	Type	Null	Default	Comments
item_id	int(11)	No		The primary identifier of the item.
value	int(11)	Yes	NULL	The field's value for this item.

search_api_db_product_display_search_api_aggregation_1

Column	Type	Null	Default	Comments
item_id	int(11)	No		The primary identifier of the item.
word	varchar(50)	No		The text of the indexed token.
score	float	No		The score associated with this token.

search_api_db_product_display_search_api_aggregation_2

Column	Type	Null	Default	Comments
item_id	int(11)	No		The primary identifier of the item.
word	varchar(50)	No		The text of the indexed token.
score	float	No		The score associated with this token.

search_api_db_product_display_search_api_aggregation_3

Column	Type	Null	Default	Comments
item_id	int(11)	No		The primary identifier of the item.

word	varchar(50)	No		The text of the indexed token.
score	float	No		The score associated with this token.

search_api_db_product_display_search_api_aggregation_4

Column	Type	Null	Default	Comments
item_id	int(11)	No		The primary identifier of the item.
word	varchar(50)	No		The text of the indexed token.
score	float	No		The score associated with this token.

search_api_db_product_display_search_api_aggregation_5

Column	Type	Null	Default	Comments
item_id	int(11)	No		The primary identifier of the item.
word	varchar(50)	No		The text of the indexed token.
score	float	No		The score associated with this token.

search_api_db_product_display_search_api_aggregation_6

Column	Type	Null	Default	Comments
item_id	int(11)	No		The primary identifier of the item.
word	varchar(50)	No		The text of the indexed token.
score	float	No		The score associated with this token.

search_api_db_product_display_search_api_aggregation_7

Column	Type	Null	Default	Comments
item_id	int(11)	No		The primary identifier of the item.
word	varchar(50)	No		The text of the indexed token.
score	float	No		The score associated with this token.

search_api_db_product_display_search_api_language

Column	Type	Null	Default	Comments
item_id	int(11)	No		The primary identifier of the item.
value	varchar(255)	Yes	NULL	The field's value for this item.

search_api_db_product_display_status

Column	Type	Null	Default	Comments
item_id	int(11)	No		The primary identifier of the item.
value	int(11)	Yes	NULL	The field's value for this item.

search_api_db_product_display_title_field

Column	Type	Null	Default	Comments
item_id	int(11)	No		The primary identifier of the item.
value	varchar(255)	Yes	NULL	The field's value for this item.

search_api_db_product_display_type

Column	Type	Null	Default	Comments
item_id	int(11)	No		The primary identifier of the item.
value	varchar(255)	Yes	NULL	The field's value for this item.

search_api_index

Table comments: Stores all search indexes on a search_api_server.

Column	Type	Null	Default	Comments
id	int(10)	No		An integer identifying the index.
name	varchar(50)	No		A name to be displayed for the index.
machine_name	varchar(50)	No		The machine name of the index.
description	text	Yes	NULL	A string describing the index' use to users.

server	varchar(50)	Yes	<i>NULL</i>	The search_api_server.machine_name with which data should be indexed.
item_type	varchar(50)	No		The type of items stored in this index.
options	mediumtext	No		An array of additional arguments configuring this index.
enabled	tinyint(4)	No	1	A flag indicating whether this index is enabled.
read_only	tinyint(4)	No	0	A flag indicating whether to write to this index.
status	tinyint(4)	No	1	The exportable status of the entity.
module	varchar(255)	Yes	<i>NULL</i>	The name of the providing module if the entity has been defined in code.

search_api_item

Table comments: Stores the items which should be indexed for each index,...

Column	Type	Null	Default	Comments
item_id	int(10)	No		The item's entity id (e.g. node.nid for nodes).
index_id	int(10)	No		The search_api_index.id this item belongs to.
changed	bigint(20)	No	1	Either a flag or a timestamp to indicate if or when the item was changed since it was last indexed.

search_api_server

Table comments: Stores all search servers created through the Search API.

Column	Type	Null	Default	Comments
id	int(10)	No		The primary identifier for a server.
name	varchar(50)	No		The displayed name for a server.
machine_name	varchar(50)	No		The machine name for a server.
description	text	Yes	<i>NULL</i>	The displayed description for a server.
class	varchar(50)	No		The id of the service class to use for this server.
options	mediumtext	No		The options used to configure the service object.
enabled	tinyint(4)	No	1	A flag indicating whether the server is enabled.
status	tinyint(4)	No	1	The exportable status of the entity.
module	varchar(255)	Yes	<i>NULL</i>	The name of the providing module if the entity has been defined in code.

search_api_sort

Table comments: Stores all activated or configured sorts of a site.

Column	Type	Null	Default	Comments
id	int(10)	No		The primary identifier for a sort.
identifier	varchar(255)	No		The identifier for this sort.
index_id	varchar(50)	No		The search_api_index.machine_name this sort belongs to.
field	varchar(255)	No		The index field this sort belongs to.
name	varchar(80)	No		The human-readable name to be displayed for this sort.
enabled	tinyint(4)	No	1	A flag indicating whether the sort is enabled.
default_sort	tinyint(4)	No	0	A flag indicating whether the sort is the default sort for the index.
default_sort_no_terms	tinyint(4)	No	0	A flag indicating whether the sort is the default sort for the index when there are no search terms present.
default_order	varchar(4)	No	desc	The default order for this field.
weight	tinyint(4)	No	0	A weight field determining the sort order of the sorts in the block.
status	tinyint(4)	No	1	The exportable status of the entity.
module	varchar(255)	Yes	<i>NULL</i>	The name of the providing module if the entity has been defined in code.

semaphore

Table comments: Table for holding semaphores, locks, flags, etc. that...

Column	Type	Null	Default	Comments
name	varchar(255)	No		Primary Key: Unique name.
value	varchar(255)	No		A value for the semaphore.
expire	double	No		A Unix timestamp with microseconds indicating when the semaphore should expire.

sequences

Table comments: Stores IDs.

Column	Type	Null	Default	Comments
value	int(10)	No		The value of the sequence.

sessions

Table comments: Drupal's session handlers read and write into the...

Column	Type	Null	Default	Comments
uid	int(10)	No		The users.uid corresponding to a session, or 0 for anonymous user.
sid	varchar(128)	No		A session ID. The value is generated by Drupal's session handlers.
ssid	varchar(128)	No		Secure session ID. The value is generated by Drupal's session handlers.
hostname	varchar(128)	No		The IP address that last used this session ID (sid).
timestamp	int(11)	No	0	The Unix timestamp when this session last requested a page. Old records are purged by PHP automatically.
cache	int(11)	No	0	The time of this user's last post. This is used when the site has specified a minimum_cache_lifetime. See cache_get().
session	longblob	Yes	NULL	The serialized contents of \$_SESSION, an array of name/value pairs that persists across page requests by this session ID. Drupal loads \$_SESSION from here at the start of each request and saves it at the end.

system

Table comments: A list of all modules, themes, and theme engines that are...

Column	Type	Null	Default	Comments
filename	varchar(255)	No		The path of the primary file for this item, relative to the Drupal root; e.g. modules/node/node.module.
name	varchar(255)	No		The name of the item; e.g. node.
type	varchar(12)	No		The type of the item, either module, theme, or theme_engine.
owner	varchar(255)	No		A theme's 'parent'. Can be either a theme or an engine.
status	int(11)	No	0	Boolean indicating whether or not this item is enabled.
bootstrap	int(11)	No	0	Boolean indicating whether this module is loaded during Drupal's early bootstrapping phase (e.g. even before the page cache is consulted).
schema_version	smallint(6)	No	-1	The module's database schema version number. -1 if the module is not installed (its tables do not exist); 0 or the largest N of the module's hook_update_N() function that has either been run or existed when the module was first installed.
weight	int(11)	No	0	The order in which this module's hooks should be invoked relative to other modules. Equal-weighted modules are ordered by name.
info	blob	Yes	NULL	A serialized array containing information from the module's .info file; keys can include name, description, package, version, core, dependencies, and php.

taxonomy_index

Table comments: Maintains denormalized information about node/term...

Column	Type	Null	Default	Comments
nid	int(10)	No	0	The node.nid this record tracks.
tid	int(10)	No	0	The term ID.
sticky	tinyint(4)	Yes	0	Boolean indicating whether the node is sticky.
created	int(11)	No	0	The Unix timestamp when the node was created.

taxonomy_menu

Table comments: Links a taxonomy term to a menu item.

Column	Type	Null	Default	Comments
mlid	int(10)	No	0	The taxonomy terms menu_link.mlid.

tid	int(10)	No	0	Tid that is linked to the mid.
vid	int(10)	No	0	Vid for the tid.

taxonomy_term_data

Table comments: Stores term information.

Column	Type	Null	Default	Comments
tid	int(10)	No		Primary Key: Unique term ID.
vid	int(10)	No	0	The taxonomy_vocabulary.vid of the vocabulary to which the term is assigned.
name	varchar(255)	No		The term name.
description	longtext	Yes	NULL	A description of the term.
format	varchar(255)	Yes	NULL	The filter_format.format of the description.
weight	int(11)	No	0	The weight of this term in relation to other terms.

taxonomy_term_hierarchy

Table comments: Stores the hierarchical relationship between terms.

Column	Type	Null	Default	Comments
tid	int(10)	No	0	Primary Key: The taxonomy_term_data.tid of the term.
parent	int(10)	No	0	Primary Key: The taxonomy_term_data.tid of the term's parent. 0 indicates no parent.

taxonomy_vocabulary

Table comments: Stores vocabulary information.

Column	Type	Null	Default	Comments
vid	int(10)	No		Primary Key: Unique vocabulary ID.
name	varchar(255)	No		Name of the vocabulary.
machine_name	varchar(255)	No		The vocabulary machine name.
description	longtext	Yes	NULL	Description of the vocabulary.
hierarchy	tinyint(3)	No	0	The type of hierarchy allowed within the vocabulary. (0 = disabled, 1 = single, 2 = multiple)
module	varchar(255)	No		The module which created the vocabulary.
weight	int(11)	No	0	The weight of this vocabulary in relation to other vocabularies.

url_alias

Table comments: A list of URL aliases for Drupal paths; a user may visit...

Column	Type	Null	Default	Comments
pid	int(10)	No		A unique path alias identifier.
source	varchar(255)	No		The Drupal path this alias is for; e.g. node/12.
alias	varchar(255)	No		The alias for this path; e.g. title-of-the-story.
language	varchar(12)	No		The language this alias is for; if 'und', the alias will be used for unknown languages. Each Drupal path can have an alias for each supported language.

users

Table comments: Stores user data.

Column	Type	Null	Default	Comments
uid	int(10)	No	0	Primary Key: Unique user ID.
name	varchar(60)	No		Unique user name.
pass	varchar(128)	No		User's password (hashed).
mail	varchar(254)	Yes		User's e-mail address.
theme	varchar(255)	No		User's default theme.
signature	varchar(255)	No		User's signature.
signature_format	varchar(255)	Yes	NULL	The filter_format.format of the signature.
created	int(11)	No	0	Timestamp for when user was created.

access	int(11)	No	0	Timestamp for previous time user accessed the site.
login	int(11)	No	0	Timestamp for user's last login.
status	tinyint(4)	No	0	Whether the user is active(1) or blocked(0).
timezone	varchar(32)	Yes	NULL	User's time zone.
language	varchar(12)	No		User's default language.
picture	int(11)	No	0	Foreign key: file_managed.fid of user's picture.
init	varchar(254)	Yes		E-mail address used for initial account creation.
data	longblob	Yes	NULL	A serialized array of name value pairs that are related to the user. Any form values posted during user edit are stored and are loaded into the \$user object during user_load(). Use of this field is discouraged and it will likely disappear in a future...

users_roles

Table comments: Maps users to roles.

Column	Type	Null	Default	Comments
uid	int(10)	No	0	Primary Key: users.uid for user.
rid	int(10)	No	0	Primary Key: role.rid for role.

variable

Table comments: Named variable/value pairs created by Drupal core or any...

Column	Type	Null	Default	Comments
name	varchar(128)	No		The name of the variable.
value	longblob	No		The value of the variable.

views_display

Table comments: Stores information about each display attached to a view.

[localhost](#) » [ck2](#)

Structure	SQL	Search	Query	Export	Import	Operations	Privileges	Routines	Event
id	varchar(64)	No							
display_title	varchar(64)	No							
display_plugin	varchar(64)	No							
position	int(11)	Yes	0						
display_options	longtext	Yes	NULL						

views_view

Table comments: Stores the general data for a view.

Column	Type	Null	Default	Comments
vid	int(10)	No		The view ID of the field, defined by the database.
name	varchar(128)	No		The unique name of the view. This is the primary field views are loaded from, and is used so that views may be internal and not necessarily in the database. May only be alphanumeric characters plus underscores.
description	varchar(255)	Yes		A description of the view for the admin interface.
tag	varchar(255)	Yes		A tag used to group/sort views in the admin interface
base_table	varchar(64)	No		What table this view is based on, such as node, user, comment, or term.
human_name	varchar(255)	Yes		A human readable name used to be displayed in the admin interface
core	int(11)	Yes	0	Stores the drupal core version of the view.

watchdog

Table comments: Table that contains logs of all system events.

Column	Type	Null	Default	Comments
wid	int(11)	No		Primary Key: Unique watchdog event ID.

uid	int(11)	No	0	The users.uid of the user who triggered the event.
type	varchar(64)	No		Type of log message, for example "user" or "page not found."
message	longtext	No		Text of log message to be passed into the t() function.
variables	longblob	No		Serialized array of variables that match the message string and that is passed into the t() function.
severity	tinyint(3)	No	0	The severity level of the event; ranges from 0 (Emergency) to 7 (Debug)
link	varchar(255)	Yes		Link to view the result of the event.
location	text	No		URL of the origin of the event.
referer	text	Yes	<i>NULL</i>	URL of referring page.
hostname	varchar(128)	No		Hostname of the user who triggered the event.
timestamp	int(11)	No	0	Unix timestamp of when event occurred.
